


# Eaton 031475

Catalog Number: 031475

Eaton Moeller® series FS Front plate, For use with T5B, T5, P3, 84 x 84 (for frame 88 x 88) mm

General specifications



Product Name	Catalog Number
Eaton Moeller® series FS Accessory	031475
Front plate	EAN
	4015080314752
Product Length/Depth	Product Height
86 mm	1 mm
Product Width	Product Weight
86 mm	0.003 kg
Certifications	
UL/CSA certification not required	

## Product specifications

### Used with

T5B, T5, P3

### Type

Front plates

### Product Category

Emergency switching off/emergency stop front plates

#### 10.10 Temperature rise

Not applicable.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

##### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

##### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

##### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

## Resources

### Brochures

[Brochure - T Rotary Cam switch and P Switch-disconnector](#)

### Catalogs

[P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

### Drawings

[eaton-rotary-switches-fs-front-plate-3d-drawing.eps](#)

115K218

### Installation videos

[Eaton's P Switch-disconnectors used in a factory](#)

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### Accessory/spare part type

Device labeling system

### Ambient operating temperature - max

50 °C

### Ambient operating temperature - min

-25 °C

### Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

### Heat dissipation capacity P<sub>diss</sub>

0 W

### Heat dissipation per pole, current-dependent P<sub>vid</sub>

0 W

### Rated operational current for specified heat dissipation (I<sub>n</sub>)

0 A

### Static heat dissipation, non-current-dependent P<sub>vs</sub>

0 W



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)