



PRODUCT-DETAILS

# OT200KAUR6AZ

## OT200KAUR6AZ Safety switch



| General Information   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OT200KAUR6AZ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product ID            | 1SCA022542R5590                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| EAN                   | 6417019171173                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Catalog Description   | OT200KAUR6AZ Safety switch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Long Description      | <p>Safety switch, 6-p. 415V AC23 200A, 110kW. Mounted auxiliary contact: 4NO2NC. Steel sheet enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking.</p> <p>The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallell cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermography.</p> |

| Material Compliance                         |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                           | 1SCC340076D0201                                                        |
| RoHS Declaration                            | 1SCC340075D0201                                                        |
| RoHS Information                            | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

|                                        |                 |
|----------------------------------------|-----------------|
| Toxic Substances Control<br>Act - TSCA | 1SCC340095D0201 |
|----------------------------------------|-----------------|

Popular Downloads

|                                      |                       |
|--------------------------------------|-----------------------|
| Data Sheet, Technical<br>Information | 1SCC340015C0201       |
| Instructions and Manuals             | 1SCC340016M0005       |
| Mechanical Drawings                  | OTKM608023PBL8RDD.stp |

Environmental

|                      |                        |
|----------------------|------------------------|
| Degree of Protection | acc. to IEC 60529 IP65 |
| Pollution Degree     | 3                      |

Ordering

|                                   |          |
|-----------------------------------|----------|
| Minimum Order Quantity            | 1 piece  |
| Customs Tariff Number             | 85363090 |
| Country or Territory of<br>Origin | Finland  |

Dimensions

|                               |         |
|-------------------------------|---------|
| Product Net Width             | 800 mm  |
| Product Net Height            | 600 mm  |
| Product Net Depth /<br>Length | 230 mm  |
| Product Net Weight            | 34.5 kg |

Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 815 mm        |
| Package Level 1 Depth /<br>Length | 910 mm        |
| Package Level 1 Height            | 325 mm        |
| Package Level 1 Gross<br>Weight   | 39 kg         |
| Package Level 1 EAN               | 6417019171173 |

Technical

|                                                     |                                                                           |
|-----------------------------------------------------|---------------------------------------------------------------------------|
| Cable Entry Position                                | Bottom/Bottom                                                             |
| Cable Outlets Per Side                              | Blank / 8xring-flange, Knock-outs: 3x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm |
| Color                                               | RAL7032                                                                   |
| Connecting Capacity Main<br>Circuit                 | Hole Diameter 8 mm<br>Screw Clamp / PE Terminal 4pc,10 ... 70 mm²         |
| Conventional Thermal<br>Current (I <sub>the</sub> ) | Fully Enclosed 200 A                                                      |
| Degree of Protection                                | acc. to IEC 60529 IP65                                                    |
| Enclosure Material                                  | Steel sheet                                                               |
| Handle Color                                        | Red / Yellow                                                              |
| Handle Type                                         | Pistol handle                                                             |
| Impact Resistance Rating                            | Housing IK09                                                              |

|                                                             |                                                            |
|-------------------------------------------------------------|------------------------------------------------------------|
| Maximum Mounted Auxiliary Contacts                          | 4 NO, 2 NC                                                 |
| Mounted Auxiliary Contacts                                  | 4 NO, 2 NC                                                 |
| Neutral Type                                                | No Neutral Terminal                                        |
| Number of Auxiliary Contacts NC                             | 2                                                          |
| Number of Auxiliary Contacts NO                             | 4                                                          |
| Number of Poles                                             | 6P                                                         |
| Pollution Degree                                            | 3                                                          |
| Power Loss                                                  | at Rated Operating Conditions per Pole 4 W                 |
| Rated Conditional Short-Circuit Current ( $I_{nc}$ )        | 40.5 kA                                                    |
| Rated Insulation Voltage ( $U_i$ )                          | 750 V                                                      |
| Rated Operational Current AC-22A ( $I_e$ )                  | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-23A ( $I_e$ )                  | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Power AC-23A ( $P_e$ )                    | (380 ... 415 V) 110 kW<br>(500 V) 132 kW<br>(690 V) 160 kW |
| Rated Operational Voltage                                   | Main Circuit 1000 V                                        |
| Rated Short-Circuit Making Capacity ( $I_{cm}$ )            | (1000 V AC) 30 kA                                          |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | for 1 s 8 kA                                               |
| Recommended Screw Driver                                    | Main Circuit M8                                            |
| Standards                                                   | IEC 60947-1, -3                                            |
| Tightening Torque                                           | Main Circuit 22 N·m                                        |

## Technical UL/CSA

|                          |                     |
|--------------------------|---------------------|
| Recommended Screw Driver | Main Circuit M8     |
| Tightening Torque        | Main Circuit 22 N·m |

## Certificates and Declarations

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC340025D2704 |
|--------------------------------|-----------------|

## External Classifications and Standards

|                                    |                                                             |
|------------------------------------|-------------------------------------------------------------|
| Object Classification Code         | Q                                                           |
| ETIM 9                             | EC000216 - Switch disconnecter (low voltage)                |
| ETIM 10                            | EC000216 - Switch disconnecter (AC)                         |
| UNSPSC                             | 39122205                                                    |
| IDEA Granular Category Code (IGCC) | 5166 >> Safety switch                                       |
| eClass                             | V11.1 : 27371403                                            |
| WEEE Category                      | 4. Large Equipment (Any External Dimension More Than 50 cm) |

---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

