DMG600 - DMG610 Datasheet



| Order code | Description | Qty per pkg | Wt |
|------------|-------------|-------------------|------|
| | | n° | [kg] |

| Inputs and ou | tputs. | | |
|---------------|---|---|-------|
| EXP10 00 | 4 digital inputs, opto-isolated | 1 | 0.060 |
| EXP10 01 | 4 static outputs, opto-isolated | 1 | 0.054 |
| EXP10 02 | 2 digital inputs and 2 static outputs, opto-isolated | 1 | 0.058 |
| EXP10 08 | 2 opto-isolated digital inputs and 2 relay outputs rated 5A 250VAC | 1 | 0.058 |

Communication ports.

| EXP10 10 | Opto-isolated USB interface | 1 | 0.060 |
|----------|---|---|-------|
| EXP10 11 | Opto-isolated RS232 interface | 1 | 0.040 |
| EXP10 12 | Opto-isolated RS485 interface | 1 | 0.050 |
| EXP10 13 | Opto-isolated Ethernet interface with Web server function | 1 | 0.060 |
| CX 01 | PC ← LOVATO Electric product connecting cable, with USB optic connector for programming, data download, diagnostics and firmware upgrade | 1 | 0.090 |
| CX 02 | PC ← LOVATO Electric product Wi-Fi connecting device for programming, data download, diagnostics and firmware upgrade | 1 | 0.090 |

CX 01

This USB/optical connector, complete with cable, allows to connect compatible Lovato Electric products with a PC without having to disconnect the the power supply from the electric panel.

The PC identifies the connection as a standard USB.

CX 02

With a Wi-Fi point connection, the LOVATO Electric products can be viewed by a PC, smartphone and tablet without having to connect cables.

General characteristics

EXP series expansion modules can increase the functionality of the LOVATO Electric products, such as:

- Digital inputs
- Relay outputs
- Static outputs
- Analog inputs
- · Inputs for PT100 temperature sensor
- Analog outputs
- · Communication interface
- GPRS/GSM modem (without antenna, see page 28-4)
- · Data storage.
- Powered directly by the base product
- Automatic identification by the base product
- Rear base product mounting with no need of tools.

Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (File E93601), as Listed Accessory under Auxiliary Devices; EXP10 08 and EXP10 18 excluded. Compliant with standards:

- For EXP10 18: IEC/EN 61850 and Italian CEI 0-16, CEI 0-20
- For EXP10 04 and EXP10 10: IEC/EN 61010-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4, UL508, CSA C22.2 n° 14
- For EXP10 15: IEC/EN 61010-1, IEC/EN 62311,
 ETSI EN 301 489-1, ETSI EN 301 469-7, EN 301511,
 USA/FCC 47 CFR part 15, Subpart B, CAN/ICES-003
- For all other types: IEC/EN 61010-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, UL508, CSA C22.2 n° 14

For overall dimensions, wiring diagrams and technical characteristics, consult the technical instructions in Downloads of the local or global websites; see details on inside front cover.

Expansion module fixing

