

Powerpact 4 - Molded Case Circuit Breaker - 1P - 100A - 230 V - L3

Local distributor code: 386962846

MGP1001L3

! Discontinued on: 3 Nov 2022

EAN Code: 3606486440360

Main

Range of product	PowerPacT 4	
Product or component type	Circuit breaker	
Device application	Distribution	
Poles description	1P	
[In] rated current	100 A at 40 °C	
[Ue] rated operational voltage	230 V AC 50/60 Hz	
Suitability for isolation	Yes conforming to BS EN 60947-2	
Utilisation category	Category A	
[Icu] rated ultimate short-circuit breaking capacity	25 kA lcu at 230 V AC 50/60 Hz	
Trip unit name	TM-D	
Trip unit technology	Thermal-magnetic	
Trip unit protection functions	Ц	
control type	Toggle	
Circuit breaker mounting mode	Panel-mounted Panel-mounted	

Complementary

[Ui] rated insulation voltage	750 V	
[Uimp] rated impulse withstand voltage	8 kV	
[lcs] rated service short-circuit breaking capacity	25 kA at 230 V AC 50/60 Hz	
Mechanical durability	20000 cycles	
Electrical durability	20000 cycles at 277 V In/2 10000 cycles at 277 V In	
Mounting support	Backplate	
Mounting position	Horizontal and vertical	
Phase connection	L3	
Number of modules	1 module(s)35 mm	
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)	
Trip unit rating	100 A at 40 °C	
Thermal protection adjustment range	100 A	
Earth-leakage protection	Without	

Environment

Standards BS EN 60947-2

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

8		
	EU RoHS Directive	Compliant
	PVC free	Yes