



NOTE1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
 2. () IS REFERENCE DIMENSION.
 3. REFER TO THE DF59S SERIES MATING/UNMATING OPERATION INSTRUCTION MANUAL (ETAD-H0651) FOR THE OPERATING OF THE PRODUCT.
 4 THE LOCK SIDE MOUNTS TO THE DIRECTION OF PCB END SIDE.

1	PHOSPHOR BRONZE	SURFACE:TIN PLATING 1μm MIN UNDER PLATING:Cu PLATING 0.3μm MIN	4 PS 3 POLYESTER 2 PS	REEL, BLACK CLEAR(COVER TAPE) CLEAR(EMBOSSED CARRIER TAPE)	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS		SCALE	COUNT	DESCRIPTION OF REVISIONS	
mm		5 : 1	2	DIS-H-007918	
HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA 12.11.14 CHECKED : OM. MIYAMOTO 12.11.14 DESIGNED : KT. ISHII 12.11.13 DRAWN : KT. ISHII 12.11.13	DESIGNED	CHECKED	DATE
			KY. SHIMAKURA	HK. UMEHARA	13.05.24
			DRAWING NO. EDC3-342887-03		
			PART NO. DF59S-1S-V(24)		
			CODE NO. CL667-0024-6-24		