



Notice : *BOA FOAM F 30*

Index: 2

GUYARD SAS

22-24, rue Lucien Rouzet
Z.A. Villedieu sur Indre/Niherne
36250 NIHERNE FRANCE

Intermediate risks - Category II PPE

EN ISO 21420 :2020 EN 388 :2016+A1 :2018
EN 407 : 2020
EN ISO 13997 :1999

FEATURES :

- High-density polyethylene glove, stainless steel fibre, nitrile foam coating.
- Elasticated cuff with coloured overlock to indicate size. Tactile glove.
- Nitrile reinforcement in pliers. Gauge 13.
- Length 24 to 30 cm depending on size.

AVAILABLE SIZE :

- Sizes 6 to 11

PRECAUTIONS FOR USE :

- Wear gloves on dry, clean hands. It is recommended that gloves be tested before use. Actual conditions of use may differ from EU type testing.
- Before re-use, check gloves for defects, holes, tears or abnormal wear.
- Shelf life: 5 years from the date of manufacture indicated on the glove.

SAFETY COMFORT AND DEXTERITY :

- Dexterity level 5
- The glove does not contain any substances at levels
- they are known or suspected to have adverse effects on the hygiene or health of the user under the foreseeable conditions of use.

PACKAGING

- In the event of unpacking, a copy of the leaflet must be enclosed with the smallest pack.
- Bag of 10 pairs
- Box of 100 pairs.

MARKING :

- The CE mark affixed to this glove signifies compliance with the essential health and safety requirements of European Regulation 2016/425 on personal protective equipment (PPE).

en en

EN 388 :2016+A1 :2018 EN 407 :2004



4 X 4 3 F

X 1 X X X X

PERFORMANCE LEVELS :

EN 388 :2016

- Abrasion : 4/4
- Blade cut : X/5
- Tear : 4/4
- Puncture: 3/4
- Cutting by sharp objects (ISO 13997) : F/F

EN 407 :2004

- Fire behaviour X/4
- Contact heat : 1/4
- Convective heat : X/4
- Radiant heat: X/4
- Small splashes of liquid metal: X/4
- Large splashes of liquid metal: X/4

PROTECTION LIMITS

- Do not use for handling objects at temperatures above 100°C.
- Do not use for handling chemicals or liquids.

RECOMMENDED USES :

- Handling slightly sharp, dry or greasy parts.
- Industry and mechanical engineering.

MAINTENANCE AND STORAGE

- No special maintenance is recommended. Products should be stored in a cool, dry, well-ventilated place away from direct light.

END OF LIFE

- End-of-life destruction must be controlled and comply with European traceability and environmental requirements.

EU Type Certificate issued in accordance with Module B Regulation (EU) 2016/425
The EU Declaration of Conformity is available on

ZVD n° :1493
www.guyard-sa.com