


**FAG****NJ216-E-XL-TVP2**

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-TVP2,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Technical information




Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	26 mm	Width
C _r	166,000 N	Basic dynamic load rating, radial
C _{0r}	168,000 N	Basic static load rating, radial
C _{ur}	29,500 N	Fatigue load limit, radial
n _G	7,000 1/min	Limiting speed
n _{gr}	4,200 1/min	Reference speed
≈m	1.55 kg	Weight



Mounting dimensions

$d_{a \min}$	91 mm	Minimum diameter shaft shoulder
$d_{a \max}$	94 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	129 mm	Maximum diameter of housing shoulder
$d_{c \min}$	104 mm	Minimum shaft shoulder
$r_{a \max}$	2 mm	Maximum recess radius

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
s	1.3 mm	Axial displacement
E	127.3 mm	Raceway diameter outer ring
F	95.3 mm	Raceway diameter inner ring
$D_{1 \min}$	122.9 mm	Minimum rib diameter outer ring
d_1	101.5 mm	Maximum rib diameter inner ring






Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

HJ216-E	L-washer
---------	----------

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed