

# Eaton 135689

Catalog Number: 135689

Eaton Moeller® series E58 Retroreflective sensing sensor, Sn=18m, 4L, 10-30VDC, dark, NPN, PNP, M30, metal, M12

### General specifications



#### Product Name

Eaton Moeller® series E58  
Retroreflective sensor

#### Catalog Number

135689

#### EAN

4015081324828

#### Product Length/Depth

165.1 mm

#### Product Height

44.45 mm

#### Product Width

165.1 mm

#### Product Weight

0.23 kg

#### Certifications

CSA-C22.2 No. 14

IEC/EN 60947-5-2

UL

UL 508

CSA File No.: UL report applies to both  
US and Canada

UL Category Control No.: NRKH, NRKH7

CE

Certified by UL for use in Canada

UL File No.: E166051

## Product specifications

### Type

Optical sensors

### Electric connection type

Plug-in connection

### Enclosure material

Metal

### Enclosure type

Cuboid

### Operating mode

Switching principle: Dark switching

### Explosion safety category for dust

None

### Explosion safety category for gas

None

### Functions

Reflected-light beam

Short-circuit protection

Protection against wire breakage

For combination with reflector

Protection against polarity reversal

### Voltage type

DC

### Connection type

4-wire

Plug-in connection M12 x 1

### Light type

Other

### Degree of protection

NEMA 6P, 13

IP68

### Interface type

Other

### LED indicator

Status indication of Switching state: Red LED

### Switch function type

Other

## Resources

### Catalogs

Product Range Catalog Sensors – products, basic information, applications

### Declarations of conformity

DA-DC-00004657.pdf

DA-DC-00004652.pdf

### Drawings

eaton-proximity-switches-e58-diffuse-reflective-sensor-dimensions-002.eps

eaton-proximity-switches-e58-diffuse-reflective-sensor-3d-drawing.eps

### Installation instructions

IL05305003Z

Load current

Max. 100 mA (I<sub>e</sub>)

Laser protection class

None

Shock resistance

100 g, Mechanical, Shock duration 3 ms

Optical surface material

Glass

Output current (mA) - max

100 mA

Output current at protected output - max

0 mA

Rated control supply voltage (U<sub>s</sub>) at AC, 50 Hz - max

0 V

Rated control supply voltage (U<sub>s</sub>) at AC, 50 Hz - min

0 V

Rated control supply voltage (U<sub>s</sub>) at AC, 60 Hz - max

0 V

Rated control supply voltage (U<sub>s</sub>) at AC, 60 Hz - min

0 V

Rated control supply voltage (U<sub>s</sub>) at DC - max

30 V

Rated control supply voltage (U<sub>s</sub>) at DC - min

10 V

Rated switching distance (S<sub>n</sub>)

18000 mm

Reflector distance - min

0 mm

Sensor height

0 mm

Sensor length

111 mm

Switching distance - max

0 mm

Switching voltage of OSSD at state high

30 V

Transmission range of the safety field

0 m

Voltage rating - max

30 V

Safety type (IEC 61496-1)

1

Switching frequency

312 Hz

Sensing mode

Dark switching

Switching output type

PNP

Sensor material

Stainless steel

Wavelength of the sensor

0 nm

Width sensor

0 mm

Product category

E58 Harsh Duty Series

Response time

1.6 ms

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-40 °C

Diameter sensor

30 mm

Light dot size

0 mm<sup>2</sup>

Number of contact energized outputs with signalling function

0

Number of outputs (protected contact energized)

0

Number of outputs (protected semiconductor)

0

Number of outputs (semiconductor with signaling function)

2

Adjustment type

Other



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)