



tesafilm®

Product Information

BNR 59213, 59212, 59211, 59215

Product Description

A sustainable contribution: The transparent tesafilm® Paper with paper backing is highly versatile and a must-have in every household, office, or school. It can be written on and is almost invisible on light-coloured surfaces such as paper.

Sustainable Aspects

- INGEDE-12 tested: tesafilm® Paper does not affect paper and cardboard reprocessing* Paper backing material: Obtained from certified forests and other controlled sources

Product Features

- The first transparent tesafilm® with a paper backing* Almost invisible: The paper adhesive tape is unobtrusive and copy-neutral on light-coloured surfaces* Versatile: For everyday use, gift wrapping, DIY projects or labelling* Ideal for paper and book pages: The readability of texts is not impaired thanks to the read-through paper tape* Simple organisation: Can be written on with permanent markers, pencils and rollerball pens* Practical: The tape offers reliable adhesion and can be removed from most smooth surfaces* Safe and convenient household tape: Easy to tear by hand - also suitable for children* INGEDE-12 tested: tesafilm® Paper does not affect paper and cardboard reprocessing* Paper backing material: Obtained from certified forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | Paper | • Total thickness | 50 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Tensile strength | 30 N/cm | • Solvent free | yes |
| • Acid-free | yes | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | yes | • Tear resistance | no |
| • Hand tearability | yes | • Transparency | good |
| • Low noise unwinding | yes | • Unwind force n/cm | 1 N/cm |
| • Photocopy neutral | yes | • Writable | yes |



tesafilm®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>