

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### · 1.1 Product identifier

#### · Trade name: 841AR

· Other Means of Identification: Super Shield™ Nickel Conductive Paint

#### · Related Part Number:

841AR-Liquid, 841AR-15ML, 841AR-55ML, 841AR-150ML, 841AR-900ML, 841AR-3.78L

· UFI: 49K0-P0NQ-G00G-9UK5

### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the mixture Electrically conductive coating and EMI/RFI shield.

· Uses advised against Not available

### · 1.3 Details of the supplier of the safety data sheet

#### · Manufacturer/Supplier:

MG Chemicals Ltd. (Head Office)  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA  
+(1) 905-331-1396  
info@mgchemicals.com

MG Chemicals  
Heame House, 23 Bliston Street  
Sedgely Dudley DY3 1JA.  
United Kingdom  
+(44) 1663 362888

MG Chemicalst Ltd.  
Level 2, Vision Exchange, Building Territorials Street,  
Zone 1, Central Business, District,  
Birkirkara CBD 1070,  
MALTA

· Further information obtainable from: sds@mgchemicals.com

### · 1.4 Emergency telephone number:

Verisk 3E (Access code: 335388)  
+(44) 20 3514787  
+(1) 760 476 3961  
UK Toll free: +(0) 800 680 0425

Members of the public seeking specific information on poisons should contact:  
In England and Wales: NHS 111 - dial 111  
In Scotland: NHS 24 - dial 111

## SECTION 2: Hazards identification

### · 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

— GB —

**Trade name: 841AR**

(Contd. of page 1)



GHS08 health hazard

Carc. 2                      H351 Suspected of causing cancer. Route of exposure: Inhalation.  
STOT RE 1                H372 Causes damage to the respiratory system through prolonged or repeated  
   exposure. Route of exposure: Inhalation.



GHS07

Eye Irrit. 2                H319 Causes serious eye irritation.  
Skin Sens. 1              H317 May cause an allergic skin reaction.  
STOT SE 3                H336 May cause drowsiness or dizziness.  
Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

nickel powder (particle diameter < 1 mm)  
acetone  
heptan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer. Route of exposure: Inhalation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.  
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, and eye protection.  
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **Determination of endocrine-disrupting properties** Endocrine Disruptor substance  $\geq 0.1\%$  = none

(Contd. on page 3)

**Trade name: 841AR**

(Contd. of page 2)

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-01-4	nickel powder (particle diameter < 1 mm) ⚠ Carc. 2, H351; STOT RE 1, H372; ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	48.0%
CAS: 616-38-6 EINECS: 210-478-4 Index number: 607-013-00-6	dimethyl carbonate ⚠ Flam. Liq. 2, H225	16.0%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	13.0%
CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3	heptan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	10.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.0%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation:

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

If exposed or concerned: Get medical advice/attention.

#### After skin contact:

If exposed or concerned: Get medical advice or attention.

Take off immediately all contaminated clothing. Wash skin with plenty of water.

If skin irritation or rash occurs: Get medical advice or attention.

Wash contaminated clothing before reuse.

#### After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

#### After swallowing:

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

If exposed or concerned: Get medical advice or attention.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)

**Trade name: 841AR**

(Contd. of page 3)

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

#### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · For safety reasons unsuitable extinguishing agents: Water with full jet

### · 5.2 Special hazards arising from the substance or mixture

The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.

During heating or in case of fire poisonous gases are produced.

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

Prevent fire-fighting wash from entering waterway or sewer system.

Inhalation of metal fumes may cause metal fever and irritate the respiratory tract.

May produce very toxic nickel carbonyl gas in the presence of carbon monoxide in a reducing atmosphere.

#### · Hazardous combustion products:

nickel oxide fumes, tetracarbonylnickel

Carbon Oxides (CO<sub>x</sub>)

toxic metal fumes

### · 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Remove or keep away all sources of extreme heat or open flames.

Do not breathe the mist/vapors/spray/fumes.

### · 6.2 Environmental precautions:

Avoid release to the environment.

Do not allow to enter sewers/ surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Do not eat, drink, or smoke when using this product.

Ensure good ventilation/exhaustion at the workplace.

Wear protective gloves and eye protection.

Wash hands and exposed skin thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Contaminated work clothing should not be allowed out of the workplace.

Obtain, read and follow all safety instructions before use.

Do not breathe mist, vapours, spray.

(Contd. on page 5)

**Trade name: 841AR**

(Contd. of page 4)

- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Keep respiratory protective device available.
  - Use explosion-proof apparatus / fittings and spark-proof tools.
  - Ground and bond container and receiving equipment.
- **7.2 Conditions for safe storage, including any incompatibilities**
  - **Storage:**
    - **Requirements to be met by storerooms and receptacles:**
      - Store in a cool location.
      - Keep in a dry and clean area, away from incompatible substances
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**
      - Keep container tightly sealed.
      - Store in cool, dry conditions in well sealed receptacles.
      - Store locked up.
- **7.3 Specific end use(s)** See section 1.2

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

· <b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>7440-02-0 nickel powder (particle diameter &lt; 1 mm)</b>	
WEL	Long-term value: 0.5 mg/m <sup>3</sup> as Ni; Sk; Carc
<b>67-64-1 acetone</b>	
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
<b>110-43-0 heptan-2-one</b>	
WEL	Short-term value: 475 mg/m <sup>3</sup> , 100 ppm Long-term value: 237 mg/m <sup>3</sup> , 50 ppm Sk
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk

- **Additional information:**
  - The lists valid during the making were used as basis.
  - Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.
- **8.2 Exposure controls**
  - **Appropriate engineering controls** No further data; see section 7.
  - **Individual protection measures, such as personal protective equipment**
    - **General protective and hygienic measures:**
      - Keep away from foodstuffs, beverages and feed.
      - Immediately remove all soiled and contaminated clothing
      - Wash hands before breaks and at the end of work.
      - Store protective clothing separately.
      - Avoid contact with the eyes and skin.
    - **Respiratory protection:**
      - Advice should be sought from respiratory protection specialists.
      - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
      - If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

(Contd. on page 6)

**Trade name: 841AR**

(Contd. of page 5)

· **Hand protection**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses or tightly sealed goggles: EN 166

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· <b>Physical state</b>	Liquid
· <b>Form:</b>	Viscous
· <b>Colour:</b>	Dark grey
· <b>Odour:</b>	Acetone-like
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	56 °C
· <b>Flammability</b>	Highly flammable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	2 Vol % (110-43-0 heptan-2-one)
· <b>Upper:</b>	13 Vol % (67-64-1 acetone)
· <b>Flash point:</b>	-17 °C (67-64-1 acetone)
· <b>Auto-ignition temperature:</b>	315 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity at 40 °C</b>	1,460 mm <sup>2</sup> /s
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C:</b>	110 hPa
· <b>Vapour pressure at 50 °C:</b>	800 hPa
· <b>Relative density at 25 °C:</b>	1.7
· <b>Vapour density (air=1):</b>	≥2 (Air = 1)
· <b>Particle characteristics</b>	Not applicable.

(Contd. on page 7)

**Trade name: 841AR**

(Contd. of page 6)

<b>9.2 Other information</b>	
<b>Important information on protection of health and environment, and on safety.</b>	
<ul style="list-style-type: none"> <li>Ignition temperature:</li> <li>Explosive properties:</li> </ul>	Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul style="list-style-type: none"> <li>Solvent content:</li> <li>Organic solvents:</li> <li>VOC (EC)</li> <li>Solids content:</li> <li>Evaporation rate</li> </ul>	25.00 % 41.00 % 11.0 % Not determined.
<b>Information with regard to physical hazard classes</b>	
<ul style="list-style-type: none"> <li>Flammable liquids</li> </ul>	Highly flammable liquid and vapour.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity**  
The nickel can react vigorously with acids and liberate hydrogen, which can form an explosive mixture in air. Nickel may react with carbon monoxide in a reducing atmosphere to form a very toxic nickel carbonyl gas.
- 10.2 Chemical stability** Chemically stable at normal temperatures and pressures.
  - Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid**  
Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.
- 10.5 Incompatible materials:**  
Oxidizing agents  
Strong acids  
acid anhydrides
- 10.6 Hazardous decomposition products:**  
No dangerous decomposition products known.  
Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
  - Acute toxicity** Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimates)</b>		
Oral	LD50	16,700 mg/kg (rat)
Inhalative	LC50/4 h	>167 mg/kg (rabbit)
<b>616-38-6 dimethyl carbonate</b>		
Oral	LD50	13,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
<b>67-64-1 acetone</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>7,426 mg/kg (rabbit)
Inhalative	LC50/ 3 h	132 mg/L (rat)

(Contd. on page 8)

# Safety data sheet

## according to UK REACH

Page 8/12

Printing date 19.09.2024

Version number 5.01 (replaces version 5.00)

Revision: 19.09.2024

**Trade name: 841AR**

(Contd. of page 7)

110-43-0 heptan-2-one		
Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 µL/kg (rabbit)
Inhalative	LC50/4 h	>16.7 mg/kg (rabbit)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Dermal	LD/50	5 g/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/L (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Summary of Effects and Symptoms by Routes of Exposure**
  - **Eyes:**  
redness  
serious irritation
  - **Skin:**  
redness  
dry skin  
rash, allergic contact dermatitis
  - **Inhalation:**  
cough  
nausea  
sore throat  
weakness  
headache  
unconsciousness  
dizziness or drowsiness  
narcotic effects
  - **Swallowed:**  
sore throat  
irritation  
pain  
nausea  
abdominal pain  
diarrhea
- **Additional toxicological information:**
  - **Delayed and immediate effects as well as chronic effects from short and long-term exposure**  
Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.  
Chronic inhalation exposure to nickel dust, spray, or mist may damage lungs.

### 11.2 Information on other hazards

· <b>Endocrine disrupting properties</b>
None of the ingredients is listed.

(Contd. on page 9)

GB —



**Trade name: 841AR**

(Contd. of page 8)

## SECTION 12: Ecological information

### · 12.1 Toxicity

· Aquatic toxicity:	
7440-02-0 nickel powder (particle diameter < 1 mm)	
EC50/ 72 h (static)	81.5–148 mg/L (algae)
LC50 96h	15.3 mg/L (trout)
	Contains nickel of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic nickel levels that are harmful to the environment. While massive nickel is insoluble in water, its powder is considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 3 assignment of the EU.
LC50/ 48 h	0.074 mg/L (water flea)
67-64-1 acetone	
EC50/ 48 h	13,500 mg/L (daphnia)
LC50 96h	5,540 mg/L (trout)
110-43-0 heptan-2-one	
EC50/ 48 h	>100 mg/L (daphnia)
LC50 96h	131 mg/L (minnow)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

### · 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### · 12.7 Other adverse effects

- **Remark:** Harmful to fish
- **Additional ecological information:**
  - **General notes:**
    - Harmful to aquatic organisms
    - Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
    - Do not allow product to reach ground water, water course or sewage system, even in small quantities.
    - Danger to drinking water if even extremely small quantities leak into the ground.

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

- **Recommendation** This material and its container must be disposed of as hazardous waste.

· European waste catalogue	
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

(Contd. on page 10)

— GB —

**Trade name: 841AR**

(Contd. of page 9)

· **Uncleaned packaging:**



· **Recommendation:**

Containers may still present a chemical hazard/ danger when empty.

Dispose of contents in accordance with all local, regional, national, and international regulations.

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

## SECTION 14: Transport information

· <b>14.1 UN number or ID number</b> · <b>ADR, IMDG, IATA</b>	UN1263
· <b>14.2 UN proper shipping name</b> · <b>ADR, IMDG</b> · <b>IATA</b>	PAINT Paint
· <b>14.3 Transport hazard class(es)</b> · <b>ADR, IMDG, IATA</b>	 · <b>Class</b> 3 Flammable liquids. · <b>Label</b> 3
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	II
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Category</b>	Not applicable. 33 F-E, <u>S</u> -E B
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	 Limited Quantity  841AR-15ML, 841AR-55ML, 841AR-150ML, 841AR-900ML, 841AR-3.78L
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D/E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E2 Maximum net quantity per inner packaging: 30

(Contd. on page 11)

**Trade name: 841AR**

(Contd. of page 10)

	ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### · Poisons Act

· Regulated explosives precursors (Part 1)		
None of the ingredients is listed.		
· Regulated poisons (Part 2)		
None of the ingredients is listed.		
· Reportable explosives precursors (Part 3)		
67-64-1	acetone	Listed
· Reportable poisons (Part 4)		
None of the ingredients is listed.		

#### · Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

#### · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 27

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.

### · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 12)

— GB —

# Safety data sheet

## according to UK REACH

Page 12/12

Printing date 19.09.2024

Version number 5.01 (replaces version 5.00)

Revision: 19.09.2024

**Trade name: 841AR**

(Contd. of page 11)

· Classification according to Regulation (EC) No 1272/2008	
Flammable liquids	On basis of test data
Serious eye damage/irritation Skin sensitisation Carcinogenicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** Regulatory department

· **Contact:** sds@mgchemicals.com

· **Date of previous version:** 25.07.2024

· **Version number of previous version:** 5.00

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

— GB —