


TIMKEN

The Timken Company
 4500 Mt Pleasant St. NW
 N. Canton, OH 44720
 Phone: (234) 262-3000
 E-Mail: CustomerCAD@timken.com • Web site: www.timken.com

Timken Part Number 387A - 382-S, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	385
Cone Part Number	387A
Cup Part Number	382-S
Design Units	Imperial
Bearing Weight	1.40 lb 0.700 Kg
Cage Type	Stamped Steel

Dimensions

d - Bore	2.2500 in 57.150 mm
D - Cup Outer Diameter	3.8125 in 96.838 mm

B - Cone Width	0.8640 in 21.946 mm
C - Cup Width	0.7982 in 20.274 mm
T - Bearing Width	1.0000 in 25.400 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	0.14 in 3.560 mm
r - Cup Backface "To Clear" Radius²	0.090 in 2.29 mm
da - Cone Frontface Backing Diameter	2.48 in 62.99 mm
db - Cone Backface Backing Diameter	2.76 in 70.10 mm
Da - Cup Frontface Backing Diameter	3.62 in 91.90 mm
Db - Cup Backface Backing Diameter	3.43 in 87.12 mm
Ab - Cage-Cone Frontface Clearance	0.11 in 2.8 mm
Aa - Cage-Cone Backface Clearance	0.03 in 0.8 mm
a - Effective Center Location³	-0.12 in -3.00 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	6280 lbf 28000 N
C1 - Dynamic Radial Rating (1 million revolutions)⁵	24200 lbf 108000 N
C0 - Static Radial Rating	24100 lbf 107000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	3810 lbf 16900 N

Factors

K - Factor⁷	1.65
e - ISO Factor⁸	0.35
Y - ISO Factor⁹	1.69
G1 - Heat Generation Factor (Roller-Raceway)	42
G2 - Heat Generation Factor (Rib-Roller End)	15.7
Cg - Geometry Factor	0.0859

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.


⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.35
ISO Factor - Y	1.69
Bearing Weight	1.4 lb
Number of Rollers Per Row	19
Effective Center Location	-0.12 inch

TIMIKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

387A - 382-S
TS BEARING ASSEMBLY

K Factor	1.65
Dynamic Radial Rating - C90	6280 lbf
Dynamic Thrust Rating - Ca90	3810 lbf
Static Radial Rating - C0	24100 lbf
Dynamic Radial Rating - C1	24200 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY