

Think Automation and beyond...




LH1D Series Surface Mount Indicators

IDEC CORPORATION

IDEC LED Spider



New ø66 Jumbo Dome Ideal for Mounting on




Excellent Visibility
From the front and the side.




IP67 Protection
Can be used in environments subject to washdown.



Cable Wiring
Integrated wiring ensures waterproof characteristics.



Connector Wiring 
Connector types available for easy maintenance.
*Jumbo dome type only



Direct Surface Mounting
Requires only a small space behind the mounting surface, and can be installed without concern for other components behind.




Red/Green
Two-color alternate illumination available.



Three-color Alternate Illumination 
Two combinations available: red, green and white; and red, green and pure white.
*Jumbo dome type only



Seven Colors
Amber, green, pure white, red, blue, white, and yellow



Legends
Marking film can be inserted into the flat type.
*Flat type only.



Slim Profile
Can be installed in small areas. Only 10.8 mm in height.
*Flat type only.



Direct Mounting on Aluminum Frames 
Installation is improved by the increased number of mounting holes.
*Jumbo dome type only


ø66 Jumbo Dome Type



Color Variation			
Amber	Green	Pure White	Red
Blue	White	Yellow	


Two- and three-color alternate illumination also available.

Application Examples



Robot Arm Status Indicator

Indicates the operating status of the motor.




AGV Status Indicator

Can be used as a directional indicator on automatic guided vehicles.


Indicators with Excellent Visibility. Large Equipment.

With increasing awareness on safety at production sites, equipment must be designed to be clearly visible and capable of delivering correct information. With an innovative design, slim and stylish IDEC LED Spiders are ideal for various applications.





Dimensions in mm.


Dome Type



Flat Type



Two-color alternate illumination also available.




Picking System

Can be used to select picking locations.



Door Monitoring

Indicates whether a door can be opened or closed.



Roller Shutter Status Indicator


Indicates the operating status of a roller shutter.

LH Series Surface Mount Indicators

Innovative indicators with IP67 protection and integrated cable wiring.

Directly mountable on equipment and aluminum frames (jumbo dome types).

- Surface mount style does not affect the location of other components. Requires only a small space behind the mounting surface.
- Integrated cable wiring ensures waterproof characteristics. 1m, 3m, and 5m cables available. M12 connector cable (30 cm) available for jumbo dome type.



Standards	Marks	File No. or Organization
UL508 CSA C22.2 No.14		UL/c-UL File No. E68961
EN60598-2-1		TÜV SÜD
EN60598-2-1 EN60947-5-1		EC Low Voltage Directive

- subject to washdown.
- Slim design well suited for installation in small spaces.
- Excellent visibility from the front and from the side.
- Legends and symbols can be printed on marking film to customize flat type.
- Two-color alternate illumination available for all types. Three-color alternate illumination available with jumbo dome type.

Standards

- LH series surface mount indicators are approved by TÜV as class III lighting fixtures.

Type	Cable	Connector
Rated Insulation Voltage (Ui)	32V	
Rated Voltage	24V AC/DC	24V DC
Operating Voltage Range	24V AC/DC ±10%	24V DC ±10%
Rated Current	17 mA	
Maximum Current Draw	0.6W	

Specifications

- Use Class 2 power supply when using the LH1D as a UL compliant product.
- Use Class III circuit when using the LH1D as an EN compliant product.
- 24V AC, 50/60 Hz
- M12 connectors are available for jumbo dome types only.

Specifications

IP67 (IEC60529) rated. Can be used in environments




Applicable Standards	IEC60947-5-1, IEC60947-1 EN60947-5-1, EN60947-1 EN60598-2-1 UL508, CSA C22.2 No.14
Operating Temperature	-20 to +55°C (no freezing)
Operating Humidity	45 to 85% RH (no condensation)
Storage Temperature	-30 to +80°C (no freezing)
Impulse Withstand Voltage (illuminating part)	800V
Insulation Resistance	Between live and dead parts: 100 MΩ minimum
Dielectric Strength	Between live and dead parts: 2000V, 50/60 Hz, 1 minute
Pollution Degree	3
Vibration Resistance	5 to 55 Hz, amplitude 0.5 mm
Shock Resistance	1000 m/s ²
Degree of Protection	IP67 (IEC60529) NEMA Type 4X Indoor Use Only (Note)
Housing Color	Black
LED Lamp Life	Approx. 50,000 hours (When used on complete DC at 25°C, brightness reduces to 50% of the initial intensity.)
Weight	140g (jumbo dome type, 1m cable) 50g (dome type, 1m cable) 50g (flat type, 1m cable)

Type	Jumbo Dome	Dome / Flat
Illumination Colors	Single Color	A (amber), G (green), PW (pure white), R (red), S (blue), W (white), Y (yellow)
	Two-Color Alternate	A/G, A/W, A/PW, R/G, R/W, R/PW, G/W, G/PW
	Three-Color Alternate	R/G/W, R/G/PW

Type	Jumbo Dome	Dome/Flat
Cable	Single Color	UL20276, 24AWG, 3-core Cable outside diameter: ø4.1 mm Allowable cable bending radius: 24.6 mm
	Two-Color Alternate	
	Three-Color Alternate	
Connector	UL20276, 22AWG, 4-core Cable outside diameter: ø5.0 mm Allowable cable bending radius: 30 mm	
	20AWG, 4-core Cable length: 0.3m Cable outside diameter: ø6.0 mm Allowable cable bending radius: 40 mm M12 one-touch connector	

LH Series Surface Mount Indicators

Jumbo Dome Type

Shape	Types	Ordering Type No.	Illumination Color
Jumbo Dome (ø66) One color 	Cable	1m	LH1D-D3HQ4C10①
		3m	LH1D-D3HQ4C30①
		5m	LH1D-D3HQ4C50①
	Connector		LH1D-D3HQ4CN1①
Jumbo Dome (ø66) 2-color alternate 	Cable	1m	LH1D-D3HQ4C10①②
		3m	LH1D-D3HQ4C30①②
		5m	LH1D-D3HQ4C50①②
	Connector		LH1D-D3HQ4CN1①②
Jumbo Dome (ø66) 3-color alternate 	Cable	1m	LH1D-D3HQ4C10①②③
		3m	LH1D-D3HQ4C30①②③
		5m	LH1D-D3HQ4C50①②③
	Connector		LH1D-D3HQ4CN1①②③

Specify a color code in place of ① in the Type No.
Color code: A, G, PW, R, S, W, Y

Specify a color code in place of ①/② in the Type No.
Color code: R/G, G/W, R/W, A/G, A/W, R/PW, G/PW, A/PW (Two-color alternate)


Specify a color code in place of ①/②/③ in the Type No.
Color code: R/G/W, R/G/PW (Three-color alternate)

Types

Package Quantity: 1


- Color code: A (amber), G (green), PW (pure white), R (red), S (blue), W (white), Y (yellow).
- For orange, specify "A" (for amber). Top

Dimensions



61.5All

dimensions in mm.



Mounting Hole Layout

Lens Colors


	Illumination Color	Lens Color
One Color	Amber (A) Green (G) Pure White (PW) Red (R) Blue (S) White (W) Yellow (Y)	Amber Green White Red Blue White Yellow
Two-color Alternate	Red (R) / Green (G) Green (G) / White (W) Red (R) / White (W) Amber (A) / Green (G) Amber (A) / White (W) Red (R) / Pure White (PW) Green (G) / Pure White (PW) Amber (A) / Pure White (PW)	White White White White White White White White
Three-color Alternate	Red (R) / Green (G) / White (W) Red (R) / Green (G) / Pure White (PW)	White White White White

Internal Circuit

- One-color Illumination LED module (color: ①)

Cable color: White / Connector pin No. 4

Cable color: Brown / Connector pin No. 3
 Cable color: Green / Connector pin No. 2
 Connector pin No. 1




• Two-color Alternate Illumination

Cable color: White / Connector pin No. 4

Cable color: Green / Connector pin No. 2


Cable color: Brown / Connector pin No. 3
 Connector pin No. 1



• Three-color Alternate Illumination

Cable color: White / Connector pin No. 4

Cable color: Green / Connector pin No. 2




Note: For the schematic of the LED

Cable color: Yellow / Connector pin No. 1 Cable color: Brown / Connector pin No. 3

LED Module Internal Circuit

The schematic of the LED module internal circuit differ depending on the illumination color.

• Illumination color: A, R, W • Illumination color: G, PW, S





module, see "LED Module Internal Circuit" on the right.

LH Series Surface Mount Indicators

Dome Type


Types

Package Quantity: 1

Shape	Cable	Ordering Type No.	Illumination Color
Dome ø37 One Color 	1m	LH1D-D2HQ4C10 ⓪	Specify a color code in place of ⓪ in the Type No. A: amber G: green PW: pure white R: red S: blue W: white Y: yellow
	3m	LH1D-D2HQ4C30 ⓪	
	5m	LH1D-D2HQ4C50 ⓪	
Dome ø37 Red/Green 2-color alternate 	1m	LH1D-D2HQ4C10RG	R (red) / G (green) 2-color alternate illumination
	3m	LH1D-D2HQ4C30RG	
	5m	LH1D-D2HQ4C50RG	


- For orange, specify "A" (for amber).

Dimensions



Internal Circuit

• One-color Illumination




Lens Colors


Illumination Type	Illumination Color	Lens Color
One Color	Amber (A)	Amber
	Green (G)	Green
	Pure White (PW)	Clear (Note)
	Red (R)	Red
	Blue (S)	Blue
	White (W)	Clear (Note)
	Yellow (Y)	Yellow
Two-color Alternate	Red (R) / Green (G)	Clear (Note)

Note: Because lenses have a white diffusion cover inside, pure white, white, and red/green types appear white when the light is off.

• Two-color Alternate Illumination



LED Module Internal Circuit




Note: For the schematic of the LED module, see "LED Module Internal Circuit" on the right.

LH Series Surface Mount Indicators

Flat Type

Types

Package Quantity: 1

Shape	Cable	Ordering Type No.	Illumination Color
Flat 	1m	LH1D-H2HQ4C10⓪	Specify a color code in place of ⓪ in the Type No. A: amber G: green PW: pure white R: red S: blue W: white Y: yellow
	3m	LH1D-H2HQ4C30⓪	
	5m	LH1D-H2HQ4C50⓪	
Flat Red/Green	1m	LH1D-H2HQ4C10RG	R (red) / G (green) 2-color alternate illumination
	3m	LH1D-H2HQ4C30RG	

(100506)

2-color Alternate




5m

LH1D-H2HQ4C50RG

• For orange, specify "A" (for amber).


Dimensions




All dimensions in mm.

Internal Circuit

• One-color Illumination




• Two-color Alternate Illumination



Lens Colors

Illumination Type	Illumination Color	Lens Color
One Color	Amber (A)	Amber
	Green (G)	Green
	Pure White (PW)	Clear
	Red (R)	Red
	Blue (S)	Blue
	White (W)	Clear
	Yellow (Y)	Yellow
Two-color Alternate	Red/Green	Clear



Replacement Parts


Cable color: White

Cable color: Brown

Cable color: White
LED color: Green

Cable color: Brown (common)

Cable color:

Shape	Material	Ordering Type No.	Lens Color
Lens (flat type) 	Polyarylate	LH9Z-1DLH2①	For flat type. Specify a color code in place of ① in the Type No. A: amber C: clear G: green R: red S: blue Y: yellow Note: Use C (clear) lens for R / G (red/green alternate), W (white), or PW (pure white) illumination.


LH Series Surface Mount Indicators

Safety Precautions

- Do not disassemble, repair, or modify the LH1D indicator, otherwise electric shock, damage, fire, or malfunction may occur.
- Do not pull out or push in the cable of the LH1D indicator, otherwise damage may occur. Provide a slack in the cable while wiring.
- The LH1D indicator is a general-purpose and industrial electronic device. Do not use the LH1D indicator for electronic equipment which may damage the human body or threaten life in case of malfunction or failure.

Operating Instructions


- LED elements may vary in colors and brightness.
- The LH1D indicator is vulnerable to static electricity. Take sufficient protection against static electricity and spikes.
- For one-color illumination of cable types, the indicator makes a rattling sound when shaken lightly. the green wire is cut short because it is not used. When cutting the cable for shorter wiring, cut the green wire short or make sure that the green wire is not used.
- Excessive shock to the LH1D may cause damage or failure, and the internal lens may fall off even if no defects are found externally. The internal lens may have fallen off when:
 - The illumination varies greatly when viewed from the side.



When any of the above is observed, contact IDEC.

Note: Do not remove the lens.


The specified degree of protection cannot be assured when the lens is removed.



Panel Mounting


Using two M3 screws (M5 screws for jumbo dome types), install the LH1D indicator to a mounting surface. Tighten the screws to a torque of 0.6 N·m maximum (1.0 to 1.4 N·m for jumbo dome types). Mounting screws are not provided and must be supplied by the user.

Jumbo Dome Type




Note 1: Take into account the thickness of the base (10.5 mm), when selecting the length of the screws.

Dome Type



Note: The dome lens is not removable. Do not attempt to remove the lens, otherwise damage will occur.

Flat Type



Note 1: Do not install the LH1D indicator by attaching only the lens, such as by taping down the lens. Other

wise internal components may come loose, as spring washers and screw locks. Note 2: Take appropriate anti-loosening measures such as spring washers and screw locks. Note 2: Make sure that the back of the indicator is

Note 3: Install the LH1D using two M5 screws, one each

securely attached to the mounting surface, so that on the top and the bottom.


the lens cannot be easily removed.

Inserting Marking Film into Flat Type Lens


1. Insert a flat screwdriver into the groove between the base and lens.

4. Insert the edge of a marking film into the gap between the base and the dif-


Do not use flat screwdrivers with a tip width of 1.0 mm or more.




2. Twist the screwdriver and disengage the lens from the base.




3. Remove the lens from the base.



fusion plate, and place the marking film on top of the diffusion plate.




5. Install the lens. Ensure that the lens is installed snugly.



Note 1: Do not touch the gasket, as this may affect its waterproof characteristics.
Note 2: Do not touch the diffusion plate.

Markings

Legends and symbols can be printed on marking film for the flat lens. One 0.1mm-thick film can be installed. Marking film is not attached and must be supplied by the user. Recommended marking film: Polyester



Specifications and other descriptions in this catalog are subject to change without notice.



IDEC CORPORATION

IDEC CORPORATION (USA)
Tel: +1-408-747-0550 / (800) 262-IDEC (4332)

IDEC ELECTRONICS LIMITED
Tel: +44-1256-321000 E-mail: sales@uk.idec.com

IDEC (SHENZHEN) CORPORATION
Tel: +86-755-8356-2977

7-31, Nishi-Miyahara 1-Chome, Yodogawa-ku, Osaka 532-8550, Japan
Tel: +81-6-6398-2571, Fax: +81-6-6392-9731
E-mail: marketing@idec.co.jp

E-mail: opencontact@idec.com

IDEC ELEKTROTECHNIK GmbH

IDEC IZUMI (H.K.) CO., LTD.

IDEC CANADA LIMITED Tel: +49-40-25 30 54 - 0 E-mail: service@idec.de Tel: +852-2803-8989 E-mail: info@hk.idec.com Tel: +1-905-890-8561, Toll Free: (888) 317-4332 IDEC (SHANGHAI) CORPORATION IDEC TAIWAN CORPORATION

E-mail: sales@ca.idec.com

Tel: +86-21-5353-1000 E-mail: idec@cn.idec.com

Tel: +886-2-2698-3929 E-mail: service@tw.idec.com

IDEC AUSTRALIA PTY. LTD.

IDEC (BEIJING) CORPORATION

IDEC IZUMI ASIA PTE. LTD.

Tel: +61-3-9763-3244, Toll Free: 1800-68-4332 www.idec.com E-mail: sales@au.idec.com Tel: +86-10-6581-6131 Tel: +65-6746-1155 E-mail:

info@sg.idec.com

(100506)

Cat. No. EP1344-0 MAY 2010 1.7S PRINTED IN JAPAN.

