

FREEWIND S3 Vibram®



Standard EN ISO 20345 : 2011

LEMAITRE

Safety since 1974



Sizes 35 to 49

Ref. FREWS30BFVA

Product Highlights



- All-terrain shoe available with men's and women fit.



- 2,0 mm thick high strength leather (against abrasion, tearing and puncture). Tongue with gusset to avoid any infiltration of dust / stones.

- Reinforced front of the shoe and anti-abrasion scuffcap for an extended life span over time.

- Anatomical and anti-bacterial Energy+ insock: reduce feeling of fatigue, odor neutralization.



- Protective toe-cap: HDPC composite.



- Puncture-resistant midsole: high tenacity fabric "0" penetration



TRAIL VIBRAM® PU/nitrile rubber antistatic sole.



- Exclusive technical sole developed in partnership with Vibram®.
- Outdoor sole with excellent grip, Hi, HRO, suitable for harsh weather conditions (hot and cold).
- Excellent resistance to abrasion.
- Dropped heel (15 mm high) for improved safety, especially on ladders.

USE

- Construction trades, road maintenance, networks, green spaces and outdoor activities.



lemaitre-securite.com

Lemaitre takes care.



FREEWIND S3 Vibram®



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper:** water-repellent leather and reinforced anti-abrasion scuffcap
- **Tongue with gusset:** high tenacity textile
- **Lining:** 3D micro-prorous fabric

Characteristics of the sole

- **Designation:** TRAIL VIBRAM®
- **Material:** polyurethane / nitrile rubber - Vibram® antistatic
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,32 (standard $\geq 0,32$)
forward heel slip: 0,35 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,20 (standard $\geq 0,18$)
forward heel slip: 0,17 (standard $\geq 0,13$)

VARIANT



Lowwind S3 SRC
LOWWS30BFVA

Practical information

Women's fitting 35-39

Weight of one shoe size 38 :
610 g

AET N° 0075/007/161/05/16/
0555 EXT 06/09/16

Men's fitting 40-49

Weight of one shoe size 42 :
755 g

AET N° 075/007/161/05/16/
0555 EXT 01/05/16

Packaging

Sizes 35 to 44

shoebox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Sizes 45 to 49

shoebox 350 x 340 x 130 mm

carton 670 x 355 x 360 mm

5 shoeboxes per carton

Gencods

35	3237154065358	43	3237154065433
36	3237154065365	44	3237154065440
37	3237154065372	45	3237154065457
38	3237154065389	46	3237154065464
39	3237154065396	47	3237154065471
40	3237154065402	48	3237154065488
41	3237154065419	49	3237154065495
42	3237154065426		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = **SRA** + **SRB**

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

Member of
SINAMAP



DON_LS 04 TDS 0105
updated: 03/12/21