
Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Local distributor code: 396735636

A9C15414

EAN Code: 3606480374968

Main

range of product	Acti9
Device short name	iATLm
Product or component type	Latched control auxiliary
[Uc] control circuit voltage	12240 V AC 50/60 Hz maintained

Complementary

[Ui] rated insulation voltage	440 V	
[Uimp] rated impulse withstand voltage	4 kV	
Remote control type	2 entries for switch	
Mounting mode	Fixed, on right side of TL	
Mounting support	DIN rail	
9 mm pitches	1	
Height	81 mm	
Width	9 mm	
Depth	69 mm	
Colour	White	
Connections - terminals	Tunnel type terminals0.54 mm² - rigid Tunnel type terminals0.54 mm² - rigid - with cable end Tunnel type terminals14 mm² - flexible Tunnel type terminals14 mm² - flexible - with cable end	
Wire stripping length	11 mm	
Tightening torque	1 N.m	
Range compatibility	Acti9 iTL Acti9 iTLi Acti9 iTLs	
Product compatibility	ITL (16 A) ITL (32 A)	

Environment

Overvoltage category	III	
IP degree of protection	IP20 conforming to IEC 60529	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-2050 °C	

Ambient air temperature for storage	-4070 °C
Standards	EN/IEC 60669-2-2

Packing Units

r adming dimes	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	8 cm
Package 1 Length	9.4 cm
Package 1 Weight	39 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	10 cm
Package 2 Width	9 cm
Package 2 Length	27 cm
Package 2 Weight	524 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.225 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
SCIP Number	Cd66a3ab-e995-436e-8541-65ce1e0b13e2	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins