

GS1AN11
TeSys GS - auxiliary contact - 1 NC+1 NO -
front/right hand side - 50...1250 A



Main

Range of product	TeSys
Device short name	GS1AN
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	1 NC + 1 NO
Contacts operation	Instantaneous
[Ith] conventional free air thermal current	20 A at 40 °C
[Ie] rated operational current	1 A at 220 V DC-13 10 A at 230 V AC-15 12 A at 127 V AC-15 4 A at 48 V DC-13 6 A at 440 V AC-15 8 A at 400/415 V AC-15 1.2 A at 110 V DC-13

Complementary

Mechanical durability	30000 cycles
Electrical durability	30000 cycles on AC-15
Product compatibility	GS
[In] rated current	1250 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 50 A 60 A 600 A 63 A 630 A 800 A
Fuse type	BS DIN NFC
Type of operating handle	Direct frontal Direct right side External frontal External right side
Product weight	0.132 kg

Environment

Contractual warranty

Warranty period	18 months
-----------------	-----------

Auxiliary Contacts - 1 N/C + 1 N/O



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.