### **AMPMODU**


TE Internal #: 2-87962-9

PCB Mount Receptacle, Right Angle, Board-to-Board, 60 Position, 2.54 mm [.1 in] Centerline, Header & Push-Push Assembly, Gold (Au)

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: PCB Mount Receptacle

PCB Mount Orientation: Right Angle
Connector System: Board-to-Board

Number of Positions: 60
Number of Rows: 2

# **Features**

# **Product Type Features**

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Header & Push-Push Assembly
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

# **Configuration Features**

Stackable	No
PCB Mount Orientation	Right Angle
Number of Positions	60
Number of Rows	2

# **Body Features**

Connector Profile	Standard
Primary Product Color	Natural

## **Contact Features**

Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Mating Square Post Dimension	.64 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	1.27 μm[50 μin]
Contact Shape & Form	Short Point



Contact Protection Type	Closed Entry Housing
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Gold
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	3 A
Termination Features	
Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	2.92 mm[.115 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Guide Pins
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Mating Alignment	With
Housing Features	
Mating Entry Location	Side
Housing Material	Polyphenylene Sulfide (PPS)
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	6.05 mm[.238 in]
Usage Conditions	
Housing Temperature Rating	Standard
Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
Operation/Application	
Solder Process Feature	Board Standoff
Circuit Application	Signal

Packaging Features



Packaging Quantity	30
Packaging Method	Tube

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2019 (197) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Pin-in-Paste capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Customers Also Bought





















TE Part #1218157-3
BOX HDR,40 POS,w/KEYING & CUST P
/N MARK

# **Documents**

# **Product Drawings**

60 MODII HORZ DR CE 100CL/115

English

# **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-87962-9\_L.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-87962-9\_L.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-87962-9\_L.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.