

M12-PFT-CRIMP-5P-KCOD-M/F-SHLD



Image is for illustration purposes only. Please refer to product description.

Part number	21 43 300 1501
Specification	M12-PFT-CRIMP-5P-KCOD-M/F-SHLD
HARTING eCatalogue	https://harting.com/21433001501

Identification

Category	Connectors
Series	Circular connectors M12
Element	Panel feed through

Version

Gender	Male Female
Shielding	Shielded
Number of contacts	5
Coding	K-coding
Locking type	Screw locking

Technical characteristics

Rated current	12 A
Rated voltage	600 V AC
Rated impulse voltage	6 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	$>10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Tightening torque	0.8 Nm Lock nut 6 Nm Metal hoods / housings
Wrench size	18
Limiting temperature	-25 ... +85 °C



Pushing Performance
Since 1945

Technical characteristics

Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65
	IP67
	IP68
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Brass
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast

Specifications and approvals

Specifications	IEC 61076-2-111
----------------	-----------------

Commercial data

Packaging size	1
Country of origin	Czechia
European customs tariff number	85366990
GTIN	5713140227972
eCl@ss	27440103 Sensor-actuator connector chassis (sensor technology actuator)
UNSPSC 24.0	39121413