



ENGLISH

Datasheet

300MHz/200MHz/100MHz/70MHz Digital Storage Oscilloscope

Stock No. : Model :

124-1954 **IDS-2304A** 123-3550 **IDS-2204A** 123-3549 **IDS-2104A** 123-3548 **IDS-2074A**
124-0232 **IDS-2302A** 124-1953 **IDS-2202A** 124-1952 **IDS-2102A** 123-3547 **IDS-2072A**



VPO
Visual Persistence Oscilloscope

FEATURES

- 300/200/100/70MHz Bandwidth, 2 or 4 Input Channels
- 2GSa/s Maximum Real-Time Sampling Rate and 100GSa/s Equivalent Time Sampling Rate
- 2Mpoints Maximum Record length
- VPO Technology to Display Less-Frequently-Occurred Signals
- Fastest Update Rate of 80,000 Waveform Per Second
- Segmented Memory Acquisition and Waveform Search Function
- Standard Provides I²C, SPI, UART, CAN and LIN Serial Bus Trigger and Analysis Functionality
- DVM, H-expansion, Datalog and Advanced Logic Functionality



The IDS-2000A Series DSO comes along with a high-value design framework, including 2G Sa/s sampling rate, 2M points record length, 2 or 4 input channels and a large screen color LCD display, to perform very fast waveform acquisition and procession at 80,000 wfms/s update rate utilizing VPO (Visual Persistence Oscilloscope) technology.

The IDS-2000A Series, carrying bandwidths of 300MHz, 200MHz, 100MHz and 70MHz and inputs of 2 and 4 channels, makes up a family of 8 in the whole series. The 2M points record length not only enables the long time waveform storage but also plays the role as a huge database of the input signals for the post-storage waveform analysis. Two powerful functions, Waveform Search and Segmented Memory are available of the IDS-2000A Series to facilitate the search the event of interest from the long record length. Waveform search defines the waveform types for the search whereas segmented memory divides the whole record length into a number of segments. Therefore, the process of searching particular waveforms can be easier and faster.

The ping-pong waveform acquisition design and the advanced VPO-technology-based waveform procession system, greatly enhance the speed and the quality of waveform display of IDS-2000A Series at a very fast update rate of 80,000 waveforms per second.

The IDS-2000A Series is equipped with all the features that a high-tech DSO should have today. The RS-232C interface, USB ports, and Go-NoGo output are provided as standard. At a moderate cost, IDS-2000A Series is a DSO to provide high customer-value with innovative design.

APPLICATIONS

- Industrial and Educational R&D Labs
- Product Testing and Quality Assurance
- Embedded System and Mix Signal Design
- System Integration & Debugging
- Maintenance & Repair Service



SPECIFICATIONS

		IDS-2072A	IDS-2074A	IDS-2102A	IDS-2104A	IDS-2202A	IDS-2204A	IDS-2302A	IDS-2304A
VERTICAL SENSITIVITY	Channels	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT	2Ch+EXT	4Ch+EXT
	Bandwidth	DC~70MHz(-3dB)		DC~100MHz(-3dB)		DC~200MHz(-3dB)		DC~300MHz(-3dB)	
	Rise Time	5ns		3.5ns		1.75ns		1.17ns	
	Bandwidth Limit	20MHz		20MHz		20M/100MHz		20M/100M/200MHz	
	Vertical Resolution	8 bits@1M : 1mV*~10V (*: When the vertical scale is set to 1mV/div, the bandwidth limit will be set to 20MHz automatically)							
	Input Coupling	AC, DC, GND							
	Input Impedance	1MΩ // 16pF approx.							
	DC Gain Accuracy (**)	±(3% X Readout + 0.1div + 1mV) when 2mV/div or greater is selected ; ±(5% X Readout + 0.1div + 1mV) when 1mV/div is selected (**: The measurement type is average of 216 waveforms with vertical position at zero)							
	Polarity	Normal , Invert							
	Maximum Input Voltage	300Vrms , CAT I (300Vrms CAT II with GTP-150A-2/250A-2/350A-2 10:1 probe)							
	Offset Position Range	1mV/div ~ 20mV/div : ±0.5V ; 50mV/div ~ 200mV/div : ±5V ; 500mV/div ~ 2V/div : ±25V ; 5V/div~10V/div : ±250V							
	Waveform Signal Process	Normal, Average, Peak Detect, Single Sequence							
TRIGGER	Source	Ch1 ,CH2, CH3*, CH4*, Line, EXT, D0-D15** ; *four channel models only. **Logic analyzer option only.							
	Trigger Mode	Auto (Supports Roll Mode for 100 ms/div and slower), Normal, Single Sequence							
	Trigger Type	Edge, Pulse Width(Glitch), Video, Pulse Runt, Rise & Fall(Slope), Alternate, Time out, Event-Delay(1~65,535 events), Time-Delay(Duration;10ns~10s), Logic*, Bus* , *with DS2-08LA or DS2-16LA option							
	Trigger Holdoff Range	10ns ~ 10s							
	Coupling	AC, DC, LF rej. , Hf rej. , Noise rej.							
	Sensitivity	DC ~ 100MHz Approx. 1div or 1.0mV ; 100MHz ~ 200MHz Approx. 1.5div or 15mV ; 200MHz ~ 300MHz Approx. 2div or 20mV							
EXT TRIGGER	Range	±15V							
	Sensitivity	DC ~ 100MHz Approx. 100mV 100MHz ~ 200MHz Approx. 150mV ; 200MHz ~ 300MHz Approx. 150mV							
	Input Impedance	1MΩ±3%, ~16pF							
HORIZONTAL	Time Base Range	1ns/div ~ 100s/div (1-2.5 increments); ROLL : 100ms/div ~ 100s/div							
	Pre-trigger	10 div maximum							
	Post-trigger	1,000 div max (depend on time base)							
	Time Base Accuracy	±20 ppm over any ≥ 1 ms time interval							
	Real Time Sample Rate	Max. : 2GSa/s							
	ET Sample Rate	100GSa/s maximum for all models							
	Record Length	Max. : 2Mpts							
	Acquisition Mode	Normal, Average, Peak Detect, Single Sequence							
	Peak Detection	2ns (typical)							
	Average	Selectable from 2 to 256							
X-Y MODE	X-Axis Input	Channel 1 ; Channel 3* (*: four channel models only)							
	Y-Axis Input	Channel 2 ; Channel 4* (*: four channel models only)							
	Phase Shift	±3° at 100kHz							
CURSORS AND MEASUREMENT	Cursors	Amplitude, Time, Gating Available; Unit : Seconds(S), Hz(1/S), Phase (Degrees), Ratio(%)							
	Automatic Measurement	36 sets: Pk-Pk, Max, Min, Amplitude, High, Low, Mean, Cycle Mean, RMS, Cycle RMS, Area, Cycle Area, ROVShoot, FOVShoot, RPREShoot, FPREShoot, Frequency, Period, RiseTime, FallTime, +Width, -Width, Duty Cycle, +Pulses, -Pulses, +Edges, -Edges, FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF, Phase							
	Control Panel Function	Cursors measurement							
	Auto Counter	6 digits, range from 2Hz minimum to the rated bandwidth							
	Autoset	Single-button, automatic setup of all channels for vertical, horizontal and trigger systems, with undo Autoset							
	Save Setup	20set							
	Save Waveform	24set							
DISPLAY SYSTEM	TFT LCD Type	8" TFT LCD SVGA color display(LED Back-light)							
	Display Resolution	800 horizontal x 600 vertical pixels (SVGA)							
	Interpolation	Sin(x)/x & Equivalent time sampling							
	Waveform Display	Dots, Vectors, Variable persistence(16ms~10s), Infinite persistence							
	Waveform Update Rate	80,000 waveforms per second, maximum							
	Display	Display mode : YT ; XY							
	Display Graticule	8 x 10 divisions							
INTERFACE	RS-232C	DB-9 male connector							
	USB Port	USB 2.0 Full-speed host port, USB 2.0 Full-speed device port							
	Ethernet Port (LAN)	RJ-45 connector, 10/100Mbps with HP Auto-MDIX (option)							
	SVGA Video Port	SVGA output (option)							
	GPIB	GPIB module (option)							
	Go/NoGo BNC	5V Max/10mA TTL open collector output							
	Kensington Style Lock	Rear-panel security slot connects to standard Kensington-style lock							
LOGIC ANALYZER (OPTION)	Sample Rate	500MSa/s							
	Bandwidth	200MHz							
	Record Length	2M max							
	Input Channels	16 Digital (D15 - D0) or 8 Digital (D7~D0)							
	Trigger Type	Edge, Pattern, Pulse Width, Serial bus (I ² C, SPI, UART), Parallel							
	Thresholds	Quad-D0 ~ D3, D4 ~ D7... Thresholds D8~D11*, D12~D15* (*: DS2-16LA only)							
	Threshold Selections	TTL, CMOS, ECL, PECL, User Defined							
	Threshold Accuracy	±100mV							
	User-defined Threshold Range	±10V							
	Maximum Input Voltage	±40V							
	Minimum Voltage Swing	±500mV							
	Input Impedance	101KΩ probe loading 8 pF							
	Vertical Resolution	1 bit							
POWER SOURCE	Line Voltage Range	AC 100V ~ 240V, 48Hz ~ 63Hz, auto selection							
MISCELLANEOUS	Multi-Language Menu	Available							
	On-Line Help	Available							
	Time clock	Time and date, provide the date/time for saved data							
	Operation Environment	Temperature: 0°C to 50°C. Relative Humidity: ≤ 80%, 40°C or below; ≤ 45%, 41°C ~ 50°C							
DIMENSIONS & WEIGHT		380(W) X 220(H) X 145(D)mm, Approx. 4.2 kg							

Note : Three-year warranty, excluding probes & LCD display panel.

Specifications subject to change without notice.

ORDERING INFORMATION

IDS-2304A	300MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2302A	300MHz, 2-Channel, Digital Storage Oscilloscope
IDS-2204A	200MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2202A	200MHz, 2-Channel, Digital Storage Oscilloscope
IDS-2104A	100MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2102A	100MHz, 2-Channel, Digital Storage Oscilloscope
IDS-2074A	70MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2072A	70MHz, 2-Channel, Digital Storage Oscilloscope

ACCESSORIES

Quick start guide , User manual CD x 1, Power cord (UK)*1,(EU)*1
 GTP-070A-4 :70MHz (10:1/1:1) Switchable passive probe for IDS-2072A/2074A(one per channel)
 GTP-150A-2 :150MHz (10:1/1:1) Switchable passive probe for IDS-2102A/2104A(one per channel)
 GTP-250A-2 :250MHz (10:1/1:1) Switchable passive probe for IDS-2202A/2204A(one per channel)
 GTP-350A-2 :350MHz (10:1/1:1) Switchable passive probe for IDS-2302A/2304A(one per channel)

FREE DOWNLOAD

PC Software	FreeWave software
Driver	USB driver LabView driver



P. O. Box 99
 Corby
 Northants NN17 9RS
 England
 Tel: +44(0) 1536 201234