

[Request a Sample](#)

Customer Specification

PART NO. ZIP-GRP-7/8

ProductConstruction

1) Tubing Type	Expandable Sleeving
2) Tubing Material	Braided PET with Hook and Loop Closure
3) Minimum Supplied ID(In)	0.500
4) Maximum Expanded ID (In)	2.375
5) Nominal Wall Thickness +/- 0.005(In)	0.025
6) Number of Carriers	88
7) Number of Yarns	4
8) Total Number of Monofilaments	220
9) Color(s)	BLACK WITH WHITE TRACER THREAD

ProductIndustryApprovals

1) UL	VW-1	
	UZKX2	
2) CSA International	5836 01	

ProductEnvironmental

1) EU Directive 2011/65/EU(RoHS2):	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C.
2) REACH Regulation (EC 1907/2006):	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

ProductProperties

Physical & Mechanical Properties		
1) Temperature Range	-70 to 125°C	
2) Tensile Strength	85000psi, Min	ASTM D638
3) Specific Gravity	1.38, Max	ASTM D792
Electrical Properties		
Chemical Properties		
1) Water Absorption	0.15%, Max	ASTM D570
2) Corrosion(0°C, 16hrs)	no corrosion	AMS-DTL-23053
3) Fungus Resistance	Pass	AMS-DTL-23053
4) Halogen Free	Yes	
5) Lead Free	Yes	

ProductOther

Packaging	
50 FT, 25 FT	Notes
1) Melt temperature: 250C (482F)	
2) Monofilament thickness: .010 in	
3) recommended cutting method: Hot knife	

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.

RoHS-KONFORMITÄTSERKLÄRUNG

An die zuständige Abteilung:

Alpha Wire Artikelnummer: ZIP-GRP-7/8


ZIP-GRP-7/8 , RoHS-konform beginnend mit 7/1/2006 Produktion

Dieses Dokument bestätigt, dass die oben genannten Alpha Artikelnummern gemäß den Anforderungen der Richtlinie 2002/95/EC (bekannt als RoHS-Richtlinie) des Europäischen Parlaments und des Rates vom 27. Januar 2003 zur Beschränkung der Verwendung bestimmter gefährlicher Stoffe in Elektro- und Elektronikgeräten hergestellt wurden. Auf die spezifischen Definitionen und Ausweitungen dieser Richtlinie sei hingewiesen. Keine Ausnahmen sind für diesen Artikel zur Einhaltung der RoHS erforderlich. Zusätzlich garantiert Alpha, dass die angegebene Artikelnummer mit Richtlinie 2002/95/EG zur Beschränkung gefährlicher Stoffe (RoHS) und allen folgenden Änderungen, sowie der China RoHS Markierung zur Kontrolle und Reduzierung von Umweltverschmutzungen durch elektronische Produkte" Norm SJ/T 11364-2006 übereinstimmt.

Substanz	Maximaler Grenzwert
Blei	0,1 Gew.-% (1000 ppm)
Quecksilber	0,1 Gew.-% (1000 ppm)
Cadmium	0,1 Gew.-% (100 ppm)
Sechswertiges Chrom	0,1 Gew.-% (1000 ppm)
Polybromierte Biphenyle (PBB)	0,1 Gew.-% (1000 ppm)
Polybromierte Diphenylether (PBDE) , einschließlich Deca-BDE	0,1 Gew.-% (1000 ppm)

"Die Informationen in dieser Erklärung basieren auf dem besten Wissen und Kenntnisstand von Alpha Wire zum Zeitpunkt der Veröffentlichung. Die hier dargestellten Informationen dienen lediglich der allgemeinen Anleitung für die sichere Anwendung, Lagerung sowie für den sonstigen Gebrauch der Produkte oder der Geräte, mit denen diese in Verbindung gebracht werden. Diese Erklärung versteht sich nicht als Garantie oder Qualitätsvorgabe. Die rechtlichen Informationen dienen nur der Orientierung. Die Nutzer der Produkte sind selbst dafür verantwortlich, die Anwendbarkeit entsprechend geltender Gesetze und Verordnungen abhängig von ihrer individuellen Nutzung des Produktes festzustellen."

Prokurist von Alpha Wire:



Dave Watson, Leiter Engineering & QM

1/18/2019