
KEMET Part Number: R413F147000M1M

(413F147000M1M)



R41, Film, Metallized Polypropylene, Automotive Safety, 4700 pF, 20%, 300 VAC (Y2), 1000 VDC, 110°C, Lead Spacing = 10mm



I 🛱 I	Dielectric:	Metallized Polypropylene
'	Style:	Radial
♦	Features:	Automotive Grade, EMI Safety
A LL	RoHS:	Yes
	Lead:	Cut
	Qualifications:	AEC-Q200, ENEC, UL, cUL, CQC
	AEC-Q200:	Yes
ions	Charifi	a ation a

Dimensions		
L	13mm +0.2mm	
Н	11mm +0.1mm	
Т	5mm +0.2mm	
S	10mm +/-0.4mm	
LL	4mm +2mm	
F	0.6mm +/-0.05mm	

Specifications		
Capacitance:	4700 pF	
Capacitance Tolerance:	20%	
Voltage AC:	300 VAC (Y2)	
Voltage DC:	1000 VDC	
Temperature Range:	-40/+110C	
Rated Temperature:	110°C	
Dissipation Factor:	0.30% 1KHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	800 V/us	
Safety Class:	Y2	

General Information

KEMET

R41

Supplier:

Series:

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1300	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

