Eaton 266641

Catalog Number: 266641

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, left, frame size 1

General specifications



Eaton Moeller series NZM operating

element

Product Length/Depth

190 mm

Product Width

100 mm

Compliances

IEC UL/CSA

RoHS conform

Catalog Number

266641

EAN

4015082666415

Product Height

100 mm

Product Weight

0.878 kg

Certifications

CSA-C22.2 No. 5-09

UL489

UL (Category Control Number DIHS)

CE marking IEC60947

CSA (Class No. 1437-01) UL (File No. E140305) CSA (File No. 22086)

CSA certified UL listed



Product specifications

Used with

NZM1(-4)

PN1(-4)

N(S)1(-4)

Туре

Accessory

Main switch assembly kit for side panel mounting

Special features

External warning

plate/designation label can

be clipped on.

For enhanced busbar tag

shroud on the incomer side,

please order IP2X protection

against contact with a finger.

Kit for use as a main switch

Features

Standard: black / gray

Actuation of the switch on the control panel side wall

Switch mounting on mounting plate

Lockable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-switch-nzm-mccb-dimensions-012.eps eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-004.eps

Installation instructions

eaton-side-wall-actuator-nzm1-xs-xzb-il01203006z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CD-nzm1_xs

DA-CS-nzm1_xs

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects $\,$

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

External warning plate/marking plate in German/English

Door coupling rotary handle

Extension shaft

Black and yellow lightning symbol

NZM...-XV4 extension shaft

Padlock

Frame

NZM1

Activation type

Actuation on the left

Suitable for

Power circuit breaker

Switch disconnector

Cover/door type

Door interlock can also be modified in I position Door interlock lockable in the 0 position using up to 3 padlocks on the handle

Number of poles

Single-pole

Degree of protection / NEMA enclosure type

IP66

4X. 12



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia