

FEATURES

- 16/0.2mm core strands
- High performing copper conductor
- 0.5mm² CSA
- Black PVC sheath
- High performance multicore

RS PRO 12 Core Unscreened Industrial Cable, 0.5 mm² Black 100m Reel

RS Stock No.: 660-4103



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

From RS PRO, a range of unscreened multicore cables, perfect for a variety of electrical applications. Cabling which has a multicore is perfect in situations where multiple cables may seem untidy or cause tripping hazards. As each of these wires are unscreened, the cost effective solution provided, excels in multiple industries. All models are highly reliable and excellent quality.

General Specifications

Conductor Material	Tinned Copper		
Number Of Cores	12		
Screened/Unscreened	Unscreened		
Sheath Colour	Black		
Screen Type	Unscreened		
Sheath Material Polyvinyl Chloride PVC			
Insulation Material	PVC		
Drain Wire	No		
Таре	Mylar Spiral		
Coverage	≥115%		
ID Thread	Green, White/Green		
A rip cord 210 D			
Marking (3times/m)	RS 6604103 16 - 2 – 12A		
Application	Power supply for lighting, Electrical devices, Motors, Electrical connections, Risers, Lighting remote control installations, Telecontrol installations		



Electrical Specifications

American Wire Gauge	20AWG		
Core Strands	16/0.2mm		
Voltage Rating	440V		
Current Rating	2.5A		
Max. Conductor DC Resistance	<40Ω/Km		
Min. Conductor DC Resistance	>200 MΩ/Km		
Conductor Resistance	40Ω/Km		

Mechanical Specifications

Cross Sectional Area	0.5mm^2		
Outer Diameter	9.5±0.2mm		
Length	100m		
Cable Shape	Multicore		
Diameter of insulation	1.8±0.05 x 12C		


Operation Environment Specifications

Minimum Operating Temperature	-20°C			
Maximum Operating Temperature	80°C			
Operating Temperature flexing	-20°C to 80°C			

Approvals

Compliance/Certifications	IEC60332-1		
Standards Met	Defence Standard 61-12 Parts 4 and 5		





Connection Data

Core colours for up to 36 core cable:

1	Red	10	Pink	19	Yellow/Blue	28	Orange/Green
2	Blue	11	Turquoise	20	White/Blue	29	Grey/Green
3	Green	12	Grey	21	Blue/Black	30	Yellow/Brown
4	Yellow	13	Red/Blue	22	Orange/Blue	31	White/Brown
5	White	14	Green/Red	23	Green/Blue	32	Brown/Black
6	Black	15	Yellow/Red	24	Grey/Blue	33	Grey/Brown
7	Brown	16	White/Red	25	Yellow/Green	34	Yellow/Violet
8	Violet	17	Red/Black	26	White/Green	35	Violet/Black
9	Orange	18	Red/Brown	27	Green/Black	36	White/Violet