


Tous droits réservés. Toute réimpression, reproduction ou communication sans l'autorisation écrite de la propriété intellectuelle est formellement interdite. Toute réimpression, reproduction ou communication sans l'autorisation écrite de la propriété intellectuelle est formellement interdite.

All rights reserved. Reproduction or issue to third parties in any form without the written authority from the proprietor. Property of FCI. Copyright FCI.

"This LF product meets European Union Directives and other country regulations as described in GS-22-008"
Packaging as per GS-14-920





TECHNICAL SPECIFICATIONS

SHELLS	: TIN/CADMIUM/ZINC PLATED STEEL
CONTACTS DIA ON ACTIVE AREA	: Ø1 MM.
CONTACTS MATERIAL	: COPPER ALLOY
CONTACT PLATING	: GOLD OVER NICKEL (ACTIVE ZONE) : TINLEAD OVER NICKEL (TERMINATION ZONE)
FOR LEAD FREE PLATING	: 2 µ MIN.MATTE TIN TOP OVER 1.27 µMIN. : NICKEL UNDER PLATE(ON TERMINATION ZONE)
INSULATOR MATERIAL	: SELF EXTINGUISHING THERMOPLASTIC- TO UL CLASS 94 V0 : THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (Kapton or Teflon)OR PROTECTIVE METALLIC DEVICE
OPERATING TEMPERATURE	: -55°C +125°C
OPERATING CURRENT	: 5 A PER CONTACT
CONTACT RESISTANCE	: ≤10m Ω
INSULATION RESISTANCE	: ≥5000 M Ω
MAXIMUM VOLTAGE	: 1000 V.r.m.s
MECHANICAL ENDURANCE	: 200 MATINGS .
DAMP HEAT	: 21 DAYS.
WIRE SIZE	: 0.6 MM ² (AWG 20) MAX.



8630-01	M3	M3
8630-01A	M3	4-40 UNC 2
8630-01B	4-40 UNC 2A	4-40 UNC 2B

ORD-CODE	EXTERNAL THREAD	INTERNAL THREAD
----------	-----------------	-----------------



e	28/12/2004	LEAD FREE DETAILS ADDED
INDEX	DATE	REVISION DESCRIPTION

50	P	66.65	52.68	61.11	11.08	14.99	11.09	5.85	55.07	13.31	1.50	1.0
	S	66.65	52.30	61.11	10.62	14.99	11.21	6.05	55.07	13.31	1.10	0.8
37	P	68.94	55.30	63.50	8.23	12.17	11.09	5.85	57.45	10.46	1.50	1.0
	S	68.94	54.71	63.50	7.77	12.17	11.21	6.05	57.45	10.46	1.10	0.8
25	P	52.65	38.84	47.04	8.23	12.17	11.07	5.85	41.02	10.46	1.10	0.8
	S	52.65	38.25	47.04	7.77	12.17	11.21	6.05	41.02	10.46	1.10	0.8
15	P	38.76	25.12	33.32	8.23	12.17	10.99	5.85	27.25	10.46	1.10	0.8
	S	38.76	24.54	33.32	7.77	12.17	11.21	6.05	27.25	10.46	1.10	0.8
09	P	30.43	16.79	24.99	8.23	12.17	10.99	5.85	19.02	10.46	1.10	0.8
	S	30.43	16.21	24.99	7.77	12.17	11.21	6.05	19.02	10.46	1.10	0.8
SHELL SIZE	A	+0,76 0	+0,25 0	±0,12 C	+0,25 0	+0,76 0	F MAX	+0,15 0	+0,51 0	+0,51 0	±0,2 K	+0,22 0

ORDERING INFORMATION

SERIES	D B V 25 P 0 64 C T X B XXX LF	LEAD FREE
SHELL SIZE		SPECIAL CODES
E,A,B,C,D		INSULATOR COLOUR
OPTIONS		BLANK- NATURAL B - BLACK
BLANK-STANDARD		DIMPLES
F-FLOAT MOUNTING		X-ON MALE CONNECTORS ONLY
V-FEM. SCREW LOCK HEX. (UNC)		SHELL PLATING
N-THREADED FEM. SCREW LOCK M3		BLANK-ZINC T-STD. TIN / Cu
L-CLINCH NUT (M3)		OPTIONS
W-RIVETED FEM. SCREW LOCK ROUND UNC		BLANK-STANDARD H-SHIELDING TERMINATION FINGERS G-HARPOON M-METAL BRACKET C-WITHOUT BRACKET
O-CLINCH NUT (UNC)		CONTACT PLATING
NO.OF CONTACTS	09,15,25,37,50	BLANK-0.2 µAu 64 - Au FLASH 65 - 0.75 µAu 67 - 0.4 µAu
CONTACTS	P - PIN S - SOCKET	
TERMINATION TYPE	0 / BLANK - SOLDER BUCKET	

Material. REFER TECHNICAL SPECIFICATIONS				Spec ref	
Mat code.				Tolerance	
Heatreat.				LINEAR	
Plating/Finish.				ANGULAR ±1°	
Dr	Mirli K Vandanath	20/03/1999	Product Family	D-SUB	Size
Eng	Elias C Thomas	20/03/1999	Model Name		Scale
Chr	George V Joseph	28/12/2004	REL Level		
Appr	K Somasundaram	28/12/2004			
Title				Dwg no	
D- SUB SOLDER BUCKET CONNECTOR (WITH ASSEMBLY OPTIONS)				C-D-SUB-0064	
Catalog no				CAD File:	
D SERIES				Sheet 1 of 1	