



tesa[®] 4206

Product Information



Highly transparent adhesive film

Product Description

tesa[®] 4206 is based on a highly transparent PP-film backing and is coated with an extremely non-ageing and light-resistant adhesive.

tesa[®] 4206 is characterised by its smooth and low noise unwinding.

Application Fields

tesa[®] 4206 can be used for:

- packaging applications where high transparency and very good aging stability are needed
- mounting of litho films
- label protection on chemical bottles
- splicing of film (photo-printing)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing material | PP film | • Total thickness | 58 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|-------|--------------------|---------|
| • Elongation at break | 150 % | • Tensile strength | 43 N/cm |
|-----------------------|-------|--------------------|---------|

Adhesion to Values

- | | |
|---------|----------|
| • steel | 3.4 N/cm |
|---------|----------|



tesa[®] 4206

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04206>