

技术资料

Fluke 700PRV-1 泄压阀套件



主要特性

- Adjustable from 725 to 5800 PSI (50 to 200 bar)
- Preset at 2,900 psi/200 bar
- Repeatability to 10% of nominal setting
- Installs directly into the 700HTP-1 pump

产品概述: Fluke 700PRV-1 泄压阀套件

The Fluke 700PRV-1 consists of a relief valve settable from 725 to 5800 PSI (50 to 200 bar) to be used with the 700HTP-1 Hydraulic Test Pump. The 1/8" NPT male thread fits directly into the Fluke 700HTP-1 pressure pump.

To be used with the 700HTP-1 Hydraulic Test Pump. The 700PRV uses a multi-turn adjustment screw to set preload on internal disc springs. This relief valve will protect the most commonly used Fluke pressure modules and pressure instruments from damage due to accidental over-pressurization.

产品规格: Fluke 700PRV-1 泄压阀套件

Size	1.52 in by 0.62 in diameter (38 mm by 16 mm diameter)
Weight	1.6 oz (46 g)
Warranty	One year
Material	Type 303 stainless steel

型号



Fluke 700PRV-1

Fluke 700PRV-1 泄压阀套件

- One adjustable relief valve
- Instruction sheet

Fluke. 让您的工作畅通无阻。

福禄克测试仪器（上海）有限公司 电话：400-810-3435 ©2025 福禄克公司
11/2025

北京福禄克世禄仪器维修和服务有限公司 电
话：400-615-1563

未经许可，本文档禁止修改

福禄克测试仪器（上海）有限公司上海维修中心 电
话：021-54402301, 021-54401908分机269

福禄克测试仪器（上海）有限公司深圳第一特约维修点
电话：0755-86337229