

PRODUCT-DETAILS

# A42 553-120

Active Energy Class  $\pm 0,5\%$  (or C for MID meters). Reactive Energy Class  $\pm 2\%$ ;



## General Information

Extended Product Type	A42 553-120
Product ID	2CMA170519R1000
ABB Type Designation	A42 553-120
EAN	7392696705196
Catalog Description	Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$ ;

Long Description

Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Internal clock for tariff shift, Min and maximum demand, previous values and event log with timestamps. 8 channel load profile Four programmable inputs or outputs. Up to the 16th harmonics for pulses or alarm etc. M-Bus communication. Accuracy class 0,5 (or C for MID meters). The meters is IEC approved + MID approved and verified. Version for use in 690 V application.

## Ordering

E-Number (Sweden)	0980700
EAN	7392696705196
Minimum Order Quantity	1 piece
Customs Tariff Number	90283011

## Dimensions

Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.207 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	68 mm
Package Level 1 Depth / Length	94 mm
Package Level 1 Gross Weight	0.279 kg
Package Level 1 EAN	7392696705196

### Environmental

Ambient Air Temperature	Operation -40 ... +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

### Additional Information

Accuracy	Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$ .
Communication Interface	M-bus
Communication	M-Bus TP
Connecting Capacity Main Circuit	0.5 ... 10 mm <sup>2</sup>
Current Rating	6 A
Degree of Protection	IP20
Enclosure Material	Plastic
Frequency (f)	50 ... 60 Hz
Function	Electricity meter
Meter Type	Transformer connected
Mounting Type	DIN rail
Number of Phases	1
	0.801 W
Product Main Type	A42
Product Name	Electricity Meter
Rated Current ( $I_n$ )	6 A
Rated Voltage ( $U_r$ )	(Un) N-L 57.7 ... 288 V
RoHS Date	2011-44
Standards	EN 50470-3
Sub-Function	Platinum

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CMC484002M0201
Declaration of Conformity - CE	2CMC484002D0001
Environmental Information	2CMC484005D0001

Instructions and Manuals

2CMC484010M4901

RoHS Information

2CMC484006

---

## Classifications

---

ETIM 4	EC001506 - Electronic kilowatt-hour meter
ETIM 5	EC001506 - Kilowatt-hour meter
ETIM 6	EC001506 - Kilowatt-hour meter
ETIM 7	EC001506 - Kilowatt-hour meter
Object Classification Code	P
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

