

SERIES 1800 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES

TO 12 (4) A 250 V AC

single-pole	Normally closed contact (SPNC)			Normally open contact (SPNO)			Switch (SPDT)							
 	1801.6325	1801.1302	1801.1303	1801.6222	1801.1202	1801.2202	1803.1121	1803.2102	1803.2402	1803.2503	1803.5102	1803.6121	1803.6152	
Voltage lamp in V														
Actuator color / printing														
Housing color														
12 (4) A 250 V AC 1E4														
10 (4) A 250 V AC 1E4														
8 (8) A 250 V AC 5E4														
6 (4) A 250 V AC 5E4														
6 (2) A 250 V AC 1E4														
4 (3) A 250 V AC 6E3														
4 (2) A 250 V AC 1E4														
30 mA 12 V 5E4														
30 mA 12 V DC 5E4														
15 A 250 V AC 1 1/2 HP														
15 A 125 V AC 3/4 HP														
10 A 250 V AC 1/2 HP														
10 A 125 V AC 1/3 HP														
6 A 250 V AC 1/2 HP														
6 A 125 V AC 1/4 HP														
6 A 125 - 250 V AC 1/8 HP														
6 A 125 V AC 1/10 HP														
4 A 250 V AC 1/10 HP														
Connection type														
Connection description		4.8	4.8		4.8		4.8							
Inrush current in A (capacitive)														
Contact distance in mm	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	≥3	
Contact material	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag	
EN 60335 cap. 30 conform *G*														
Miscellaneous									Installation depth 13.2	Installation depth 16.2				
Stock version														