

TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 115 A - 110 V AC 50/60 Hz coil

Local distributor code:

386021619 LC1D115F7

EAN Code: 3389110377088

Main

Range	TeSys
Range of product	TeSys Deca
Product or component type	Contactor
Device short name	LC1D
Contactor application	Resistive load
	Motor control
Utilisation category	AC-3
	AC-4
	AC-1
	AC-3e
Poles description	3P
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 25400 Hz
	Power circuit: <= 300 V DC
[le] rated operational current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
	115 A (at <60 °C) at <= 440 V AC AC-3 for power circuit
	115 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	110 V AC 50/60 Hz

Complementary

Motor power kW	30 kW at 220230 V AC 50/60 Hz (AC-3) 55 kW at 380400 V AC 50/60 Hz (AC-3) 59 kW at 415440 V AC 50/60 Hz (AC-3) 75 kW at 500 V AC 50/60 Hz (AC-3) 80 kW at 660690 V AC 50/60 Hz (AC-3)	
	65 kW at 1000 V AC 50/60 Hz (AC-3) 18.5 kW at 400 V AC 50/60 Hz (AC-4) 30 kW at 220230 V AC 50/60 Hz (AC-3e) 55 kW at 380400 V AC 50/60 Hz (AC-3e) 59 kW at 415440 V AC 50/60 Hz (AC-3e) 75 kW at 500 V AC 50/60 Hz (AC-3e) 80 kW at 660690 V AC 50/60 Hz (AC-3e) 65 kW at 1000 V AC 50/60 Hz (AC-3e)	
Motor power hp	30 hp at 200/208 V AC 50/60 Hz for 3 phases motors 40 hp at 230/240 V AC 50/60 Hz for 3 phases motors 75 hp at 460/480 V AC 50/60 Hz for 3 phases motors 100 hp at 575/600 V AC 50/60 Hz for 3 phases motors	
Compatibility code	LC1D	
Pole contact composition	3 NO	
Protective cover	With	
[lth] conventional free air thermal current	al 200 A (at 60 °C) for power circuit	
Irms rated making capacity	1260 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1	

Rated breaking capacity	1100 A at 440 V for power circuit conforming to IEC 60947	
[lcw] rated short-time withstand current	250 A 40 °C - 10 min for power circuit 550 A 40 °C - 1 min for power circuit 950 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit 1100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
Associated fuse rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit 10 A gG for signalling circuit	
Average impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit	
Power dissipation per pole	24 W AC-1 7.9 W AC-3 7.9 W AC-3e	
[Ui] rated insulation voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
overvoltage category	III	
pollution degree	3	
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947	
Safety reliability level	B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Mechanical durability	8 Mcycles	
Electrical durability	0.8 Mcycles 200 A AC-1 at Ue <= 440 V 0.95 Mcycles 115 A AC-3 at Ue <= 440 V 0.95 Mcycles 115 A AC-3e at Ue <= 440 V	
Control circuit type	AC at 50/60 Hz standard	
Coil technology	Built-in bidirectional peak limiting diode suppressor	
Control circuit voltage limits	0.30.5 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.15 Uc (-4055 °C):operational AC 50/60 Hz 11.15 Uc (5570 °C):operational AC 50/60 Hz	
Inrush power in VA	280350 VA 60 Hz cos phi 0.8 (at 20 °C) 280350 VA 50 Hz cos phi 0.8 (at 20 °C)	
Hold-in power consumption in VA	/A 218 VA 60 Hz cos phi 0.3 (at 20 °C) 218 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	38 W at 50/60 Hz	
Operating time	620 ms opening 2050 ms closing	
Maximum operating rate	2400 cyc/h at 60 °C	

Connections - terminals	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: solid without cable end	
	Power circuit: connector 1 10120 mm² - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 1050 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 10120 mm² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm² - cable stiffness: solid without cable end	
Tightening torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency 25400 Hz		
linimum switching voltage 17 V for signalling circuit		
Minimum switching current	t 5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Rail	
	Plate	

Environment

Standards	CSA C22.2 No 14 EN 60947-4-1 IEC 60947-4-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1	
Product certifications	UL CSA CCC UKCA CE EAC Marine	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	

Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)	
Height	158 mm	
Width	120 mm	
Depth	136 mm	
Product weight	2.5 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.500 cm
Package 1 Width	17.500 cm
Package 1 Length	21.500 cm
Package 1 Weight	2.495 kg
Unit Type of Package 2	P06
Number of Units in Package 2	27
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	80.311 kg

Logistical informations

Country of origin CZ

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	111
Environmental Disclosure	Product Environmental Profile

Use Better


Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
SCIP Number	A530c666-91dd-4119-8d61-f1c22a361ecb	
China RoHS Regulation	China RoHS declaration	
PVC free	Yes	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Take-back	No	

Dimensions Drawings

Dimensions



(1) Minimum electrical clearance

LC1		D115 and D150 (3-pole)
а		120
	with LA4 DA2	174
b1	with LA4 DF, DT	185
	with LA4 DM, DL	188
	with LA4 DW	188
	without cover or add-on blocks	132
C	with cover, without add-on blocks	136
с1	with LAD N or C (2 or 4 contacts)	150
c2	with LA6 DK20	155
23	with LAD T, R, S	168
с3	with LAD T, R, S and sealing cover	172

Connections and Schema

Wiring

