

1457326

https://www.phoenixcontact.com/in/products/1457326

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Microfuse, nominal current: 2 A, tripping characteristics: slow-blow (T), length: 20 mm, diameter: 5 mm

Commercial data

Item number	1457326
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	BH322Y
GTIN	4063151848804
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Country of origin	DE



1457326

https://www.phoenixcontact.com/in/products/1457326

Technical data

Product properties

Product type	Fuse
Number of fuses in the set	10

Electrical properties

Tripping characteristic	slow-blow (T)
Rated voltage	250 V AC
Rated current	2 A
Maximum power dissipation for nominal condition	1.6 W

Dimensions

Dimensions	5 x 20 mm



1457326

https://www.phoenixcontact.com/in/products/1457326

Classifications

ECLASS

	ECLASS-13.0	27142001			
ΕT	ETIM				
	ETIM 9.0	EC002298			



1457326

https://www.phoenixcontact.com/in/products/1457326

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in