

CP0182A v3.11 RS 851-044

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 1

Compilation date: 22/03/2021

Revision No: 12

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN**Product code:** RS851-044**UFI:** P1P0-V0RM-6006-FE20

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: RS Components Ltd

Birchington Road

Corby

Northamptonshire

NN17 9RS

England

Tel: +44 (0) 845 850 9900**Email:** RCustomerServicesUK@rs-components.com

Glenview Industrial Estate

Herberton Road

Rialto

Dublin 12

Tel No +353 (0) 1 415 3100

enquiries.ie@rs-components.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1865 407333 (24hr)

+44 (0) 1235 239670 (24hr)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

EUH205: Contains epoxy constituents. May produce an allergic reaction.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 2



Signal words: Warning

Precautionary statements: P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash exposed skin thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P337+P313: If eye irritation persists: Get medical advice/attention.
P501: Dispose of contents/container to comply with Local, National and International regulations.

Haz. ingredients (label): BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}; BISPHENOL F

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	70-90%

2-(CHLOROMETHYL)OXIRANE; FORMALDEHYDE; PHENOL

-	28064-14-4	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411; -: EUH205	5-10%
---	------------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 4

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Slight odour

Solubility in water: Insoluble

Kinematic viscosity: 8000-15000

Viscosity test method: @25°C mPa.s

Boiling point/range°C: > 200

Flash point°C: > 150

Melting point/range°C: N/A

Relative density: 1.17@20degC

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

[cont...]

SAFETY DATA SHEET

TWIN PACK EPOXY POTTING COMPOUND (BLACK) - RESIN

Page: 7

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

CP0182B v3.11 RS 851-044

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 1

Compilation date: 17/11/2020

Revision No: 13

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HIGH STRENGTH SLOW SET EPOXY HARDENER**Product code:** RS159-3957/RS851-044 **UFI:** 4UYD-P05Y-700X-3HEW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: RS Components Ltd

Birchington Road

Corby

Northamptonshire

NN17 9RS

England

Tel: +44 (0) 845 850 9900**Email:** RCustomerServicesUK@rs-components.com

Glenview Industrial Estate

Herberton Road

Rialto

Dublin 12

Tel No +353 (0) 1 415 3100

enquiries.ie@rs-components.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1865 407333 (24hr)

+44 (0) 1235 239670 (24hr)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Skin Corr. 1B: H314; Skin Sens. 1A: H317**Most important adverse effects:** Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P264: Wash hands, forearms and face thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Haz. ingredients (label): PHENOL, STYRENATED; 2-PIPERAZIN-1-YLETHYLAMINE; BIS (ISOPROPYL)NAPHTHALENE; 2,2'-IMINODIETHYLAMINE; 2-(2-AMINOETHYLAMINO)ETHANOL (AEEA)

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PHENOL, STYRENATED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
262-975-0	61788-44-1	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Aquatic Chronic 2: H411	50-70%

2-PIPERAZIN-1-YLETHYLAMINE

205-411-0	140-31-8	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	10-30%
-----------	----------	---	--	--------

BIS(ISOPROPYL)NAPHTHALENE

254-052-6	38640-62-9	-	Aquatic Acute 1: H400; Aquatic Chronic 2: H411	5-10%
-----------	------------	---	--	-------

[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 3

2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	<1%
-----------	----------	---	---	-----

2-(2-AMINOETHYLAMINO)ETHANOL (AEEA)

203-867-5	111-41-1	-	Repr. 1B: H360FD; Skin Corr. 1B: H314; Skin Sens. 1: H317; -: H361	<1%
-----------	----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,2'-IMINODIETHYLAMINE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
-------	------------	--------------	------------	--------------

[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 5

UK	4.3 mg/m ³	-	-	-
----	-----------------------	---	---	---

DNEL/PNEC Values

Hazardous ingredients:

2,2'-IMINODIETHYLAMINE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	11.4	Workers	Local
DNEL	Inhalation	15.4	Workers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Amine-like

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Soluble

Viscosity: No data available.

Boiling point/range°C: >35

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >93

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: <5 hPa @20degC

Relative density: 0.97

pH: 8-11

VOC g/l: zero

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 6

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

PHENOL, STYRENATED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

2-PIPERAZIN-1-YLETHYLAMINE

IPR	MUS	LD50	250	mg/kg
ORL	RAT	LD50	2140	µl/kg

2,2'-IMINODIETHYLAMINE

DERMAL	RBT	LD50	1045	mg/kg
ORAL	RAT	LD50	1620	mg/kg
VAPOURS	RAT	4H LC50	0.3	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

[cont...]

SAFETY DATA SHEET
HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 7

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2,2'-IMINODIETHYLAMINE

ALGAE	72H ErC50	1164	mg/l
DAPHNIA	48H EC50	32	mg/l
FISH	96H LC50	322	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2815

14.2. UN proper shipping name

Shipping name: N-AMINOETHYLPIPERAZINE

14.3. Transport hazard class(es)

Transport class: 8 (6.1)

14.4. Packing group

Packing group: III

[cont...]

SAFETY DATA SHEET

HIGH STRENGTH SLOW SET EPOXY HARDENER

Page: 8

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H360FD: May damage fertility. May damage the unborn child.
H361: Suspected of damaging fertility or the unborn child.
H400: Very toxic to aquatic life.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.