

1101283

https://www.phoenixcontact.com/in/products/1101283

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Maintenance license (3 years) for the Emalytics Controller license NC4-100

Commercial data

Item number	1101283
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	****
Product key	DRHBAA
GTIN	4055626958118
Weight per piece (including packing)	0.001 MGM
Weight per piece (excluding packing)	0.001 MGM
Customs tariff number	49119900
Country of origin	US



1101283

https://www.phoenixcontact.com/in/products/1101283

Technical data

Product properties

roduct properties	
Product type	Building management system
Area of application	Building technology
System properties	
Type of software	Embedded
Intended use for the software	Automation
	Engineering
License information	
Type of license	Maintenance license
License duration	3 Jahre
Functionality	
Integrated function	Analysis
	Data acquisition
	Diagnostics
	Startup
	Communication
	Configuration
	Project planning
Target system	Automation station
Supported controllers	ILC 2050 BI
Number of data points (embedded)	100
Number of clients	nicht relevant

System requirements

Languages supported	German, English
Screen resolution	1024 x 768 pixel(s) ,or higher



1101283

https://www.phoenixcontact.com/in/products/1101283

Classifications

ECLASS

	ECLASS-11.0	27242590		
	ECLASS-12.0	27242590		
	ECLASS-13.0	27242590		
ETIM				
	ETIM 9.0	EC001435		
UNSPSC				
	UNSPSC 21.0	43233600		



1101283

https://www.phoenixcontact.com/in/products/1101283

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		



1101283

https://www.phoenixcontact.com/in/products/1101283

Accessories

ILC 2050 BI - Controller

2403160

https://www.phoenixcontact.com/in/products/2403160



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in